SR61 Handheld Scanner

Honeywell

contents

holders, holsters, hangers 2

batteries & chargers 3

cables 4

wireless 6

power supplies 6

power cords 7

holders, holsters, hangers

PRODUCT NAME	SKU	DESCRIPTION
Wall or Vehicle-Mount Holder	**203876-002**	Securely holds the SR61 scanner in place, whether mounted on a vehicle or to a wall. Attach to the wall with screws, or attach to a vehicle with tie-wraps. Includes all necessary installation hardware.
Hands-Free Stand	**203877-001**	Flexible gooseneck-style scanner stand. Can be screw-mounted to the countertop for additional stability. Includes all necessary installation hardware. Scanner can be set to auto-trigger hands-free mode to auto-detect and scan items.
Desktop Stand 	**203878-001**	Provides a convenient way to store the scanner when you are not using it. Includes all necessary installation hardware.
Belt Holster	**825179-001**	A comfortable way to carry the scanner when you are not using it. Attaches to either your right or left side. Adjustable belt and leg strap for one-size-fits-all comfort.
Dangle Suspension	**825181-001**	A hassle-free way to secure the scanner to your vehicle or workstation, providing you access only when you need it. Includes adjustable resting height, lift (spring tension) and drag brake. Includes dangle suspension and carabiner; does not include mounting hardware specific to your vehicle or structure.

batteries & chargers

PRODUCT NAME	SKU	DESCRIPTION
Additional Battery Pack for Standard Wireless Models		Additional lithium-ion battery pack for wireless scanners. Rated for greater than 10 hours on a full charge.
	075082-002	For wireless scanners
	318037-001	For non-incendive wireless scanners only
Desktop or Wall Charger	**852901-001**	Single-bay scanner charger ideal for mounting on a desktop or wall. Includes status light for recharge state. Does not include wall mounting hardware (varies by wall thickness). Does not include power supply; must be ordered separately (see last page).
Two-Bay Charger	**852907-001**	Two-bay scanner charger ideal for mounting on a desktop or wall. Includes status light for recharge state. Does not include wall mounting hardware (varies by wall thickness). Does not include power supply; must be ordered separately (see last page).
Four-Bay Charger	**852908-001**	Same as above, with four charging bays. Does not include power supply; must be ordered separately (see last page).
Eight-Bay Charger	**852902-001**	Same as above, with eight charging bays. Does not include power supply; must be ordered separately (see last page).

cables

PRODUCT NAME	SKU	DESCRIPTION
USB Cable, 1.98 m (6.5 ft)		Provides a USB connection to host device.
	236241-001	Requires an external power supply unit, ordered separately. For use with current SR61T models that support USB 2.0 (SR61TXR, SR61THP, SR61TL, SR61T1D and SR61T2D).
	236183-002	Requires an external power supply unit, ordered separately. For use with legacy SR61T models only (SR61TE0001, SR61TE0101, SR61TL0000, SR61TL0100, SR61TA0000 and SR61TV0000).
	236240-001	Receives power from host device. For use with current SR61T models that support USB 2.0 (SR61TXR, SR61THP, SR61TL, SR61T1D and SR61T2D).
	236182-001	Receives power from host device. For use with SR61T legacy models only (SR61TE0001, SR61TE0101, SR61TL0000, SR61TL0100, SR61TA0000 and SR61TV0000).
USB Cable, 2.44 m (8 ft), Coiled	**236219-001**	Provides a USB connection to host device. Coiled.
RS-232 Cable, 9-Pin		Provides an RS-232 serial connection to terminals providing non-powered 9-pin D sub connector. Requires external power supply unit, ordered separately.
	236185-001	1.98 m (6.5 ft)
	236198-001	3.66 m (12 ft)

PRODUCT NAME	SKU	DESCRIPTION
RS-232 Cable, Power from Host, 9-Pin		Ideal for connecting scanner to a vehicle-mount terminal (CV30, CV41, CV60, CV61). Power from host. Can also be used for connection to Honeywell handheld terminals via RS-232 adapter for all configurations.
	236184-001	1.98 m (6.5 ft)
	236197-001	3.66 m (12 ft)
Wand Emulation Cable, 1.98 m (6.5 ft), 10-Pin, Coiled	**236188-002**	For use with Honeywell 242x, 246x and 248x handheld terminals.
	236189-002	For use with Honeywell 2455 and 2475 vehicle-mount terminals. The 10-pin connector is molded to provide additional sealing.
Wand Emulation Cable, 1.98 m (6.5 ft), 9-Pin, Coiled	**236190-002**	For use with Honeywell 243x handheld terminals.
Keyboard Wedge Cable, 1.98 m (6.5 ft)	**236214-001**	For use with PCs and laptops with PS/2 style keyboard connector. Straight cable (with Y pigtail) receives power from computer, or via power supply ordered separately.

wireless

PRODUCT NAME	SKU	DESCRIPTION
Adapter, Bluetooth® to USB	**203771-001**	Enables wireless scanner connection to host PC or laptop via USB connection. Includes adapter and barcode configuration sheet.
Adapter, Bluetooth to Serial	**203768-001**	Enables wireless scanner connection to host PC or laptop via serial connection.

power supplies

PRODUCT NAME	SKU	DESCRIPTION
Universal Power Supply, 12VDC		Universal power supply for use with multi-bay chargers. Power cord ordered separately.
	851082-203	Level IV for North America, Australia or New Zealand. CEC/RoHS.
	851082-003	Not for use in North America, EMEA, Australia and New Zealand. RoHS. 50W.
Power Supply, 5VDC, 18W	**851089-206**	For use outside of EMEA. Power cord ordered separately. RoHS.
Power Supply, 12V, 48W	**851095-121**	For use in EMEA only. Power cord ordered separately.

power cords

PRODUCT NAME	SKU	DESCRIPTION
Region-Specific Power Cord, RoHS	**071918**	AC Power Cord, China
	1974027-025	AC Power Cord, Europe
	1974028-025	AC Power Cord, U.S.
	1974029-020	AC Power Cord, UK
	1974030-025	AC Power Cord, Australia
	321471-002	AC Power Cord, Italy
	321500-002	AC Power Cord, Japan
	321501-002	AC Power Cord, Denmark
	321502-002	AC Power Cord, India/South Africa

For more information:
www.honeywellaidc.com

Honeywell Scanning & Mobility
9680 Old Bailes Road
Fort Mill, SC 29707
800-582-4263
www.honeywell.com

Bluetooth is a trademark or registered trademark in the US and/or in other countries of the Bluetooth SIG, Inc.

SR61 Accessory Catalog Rev B 07/15
© 2015 Honeywell International Inc.

Honeywell