

DIRECT THERMAL/
THERMAL TRANSFER
PRINTER

EasyCoder™ 3400

Benefits:

- **Designed to Last**
Tough, rugged full metal casing is ideal for today's dynamic warehouse, distribution and manufacturing environments.
- **Economical and Reliable**
Economical price along with high reliability makes the 3400 a printer of choice for applications requiring distributed printing.
- **Flexible**
A variety of printing modes such as tear-off, label auto-peel, full batch take-up or cutter, ensure long-term flexibility.
- **Time Schedule**
The 3400 provides expanded on-board global language support and standard support of most 2D bar code symbologies.

Our best selling printer just got better. Meet your requirements for a value-priced, versatile printer with Intermec's most popular printer. The EasyCoder 3400 with its 11.43 cm (4.5") maximum label width, unlimited label length and 203 dpi resolution makes it suitable for most of today's bar code label standards. It's also reliable enough for all but the very highest production environments. Featuring metal construction, the 3400 is built for the toughest environments.

Current 3400 series users will see many enhancements over earlier 3400 series printers. The 3400 now comes with Intermec's new powerful IPL3™ printer language with GLOBE™ worldwide language support. GLOBE™ allows the printer to automatically adjust to character mapping standard, including those for Asian double-byte fonts. In addition, the UNICODE standard language and other well known character mapping standards such as ASCII, Shift-JIS, Big 5, GB and IBM Codepage are all intelligently self-managed and do not require an external font card. Popular 2D symbologies have also been added as standard features.

Overall performance of the 3400 has been enhanced. Print speed has been increased from 5"/second to 6"/second and



RS-232 serial port communication speed has been doubled. A new heavy duty cutter with tray option is available on the 3400C, not previously available on earlier models. Of course, the 3400 is fully backward compatible with 3400A/B printers and is backed with Intermec's 12 month warranty.

It all adds up to a powerful printer that is designed and built to be the right solution for the majority of industrial bar code applications.

EasyCoder™ **3400****General**

General Purpose Industrial Direct Thermal/Thermal Transfer Printer. Prints high quality bar codes on pressure sensitive labels and tags in straight through, auto-peel, and batch rewind modes.

Model

3400 Bar Code Label Printer

Physical Characteristics

Length: 27.7 cm (17.25")

Width: 43.8 cm (9.8")

Height: 24.9 cm (10.9")

Weight: 35 kg (3.5 lbs.)

Print Specifications

Element: 0.125 mm (0.00492")

Resolution: 8 dots/mm (203 dpi)

"X" Dimension: 0.13 to 1.27 mm (5 to 50 mil)

Max. Length: Unlimited

Max. Width: 104 mm (4.1")

Speed: 51, 77, 102, or 128 mm/sec (Select 2", 3", or 6")

Media Specifications

Roll: 152 m (6000" linear)

Width: 19 to 114 mm (.75 to 4.50")

Length: 13 to 610 mm (0.5 to 24"); fanfold 432 mm (17") max.

Roll Dimensions: 213 mm (8.38")

Thickness: .08 to .31 mm (0.003 to 0.012")

Core Size: 76 mm (3")

Ribbon Specifications –

Roll: 152 m (6000" linear)

Widths: 51, 77, 104 mm (2", 3", 4.1")

Communications

Rate: 1,200 to 38.4K bps

Asynchronous: RS-232C, RS-422, RS-485

Flow Control: XON/XOFF, READY/BUSY

Fonts and Graphics

Nine resident bitmapped fonts (includes OCR-A and OCR-B)

Supports user-defined fonts and graphics

Software

IPL3 is an advanced printer programming language that includes many features not available in other bar code printers

Advanced bar code algorithms handle all required encodation

Error detection protocols verify secure data transmission

Command errors and printer status are easily identified to your host.

Communicates in printable ASCII or control characters

Independent character and field rotation

Windows compatible

Globe™ support

Backward compatibility with 86XX and IPL2

Character Sets

Unicode; All single-byte codepage; All double byte codepage.

Power Supply

100, 115, 200 and 230 V AC ± 10%; 50 Hz to 60 Hz

Printer Operating Environment**Operating Temperature:**

4° to 40°C (40° to 104°F)

Storage Temperature:

0° to 49°C (32° to 120°F)

Humidity:

10 to 90% (non-condensing)

Bar Code Symbologies

UPC/EAN (UPC-A/E, EAN-8/13, ISBN Supplemental); I 2 of 5; Code 2 of 5; Codabar; Code 11; Code 16K; Code 39; Code 49; Code 93; Code 128; HIBC; POSTNET; Code One; PDF 417 and Maxicode (optional); QR Code

Standards Supported

UPC/EAN Shipping Container; UCC/EAN 128 Serial Shipping Container; MH10.8 Shipping Label; AIAG (shipping parts label); LOGMARS; POSTNET; ISBT 128

Regulatory Approvals

Complies with all FCC Part 15, Class A; CISPR 22 Class B; ICES-003 Class B; UL, CSA & TÜV-GS agency approved; CE, NOM & C-TIC

Options

Internal batch take-up adapter; Centronics® parallel; Internal IBM® Coax® adapter; Internal IBM® Twinax® adapter; Bitmap and outline Kanji/Katakana; RF Gateway (902-928 MHz); Expanded font support; Ethernet®, Novell® Netware® or TCP/IP connectivity; Cutter/tray; Memory expansion to 512K NVRAM; Storage expansion to 8 MB Flash

**Where
Information
Gets Down
To Business™**

North America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax • Norand Mobile Systems Division • 550 2nd Street S.E. • Cedar Rapids, Iowa 52401 • 1 (800) 452-2757 tel • 1 (319) 369-3453 fax • Amlech Systems Division • 19111 Dallas Parkway, Suite 300 • Dallas, Texas 75287-3106 • 1 (800) 923-4824 toll-free • 1 (972) 733-6600 tel • 1 (972) 733-6699 fax

Europe/Middle East/Africa • Sovereign House • Vastern Road • Reading, Berkshire, RG1 8BT • United Kingdom • +44 118 987 9400 tel • +44 118 987 9401 fax
Asia Pacific/Latin America • 6001 36th Avenue West • P.O. Box 4280 • Everett, Washington 98203-9280 • 1 (800) 347-2636 tel • 1 (319) 369-3324 fax

Label Products and Supplies • North America • 1 (513) 874-5882 tel • 1 (513) 874-8487 fax • or 1 (800) 227-9947 tel • 1 (800) 227-1707 fax • Latin America/Asia Pacific • 1 (513) 870-7930 Int'l phone • 1 (513) 874-3613 Int'l fax • Europe/Middle East/Africa +31 24 372 3100 tel • +31 24 378 0070 fax

World-Wide Fax Document Retrieval Service • 1 (650) 637-2603 tel • 1 (800) 755-5505 (North America Only)

Internet • www.intermec.com **E-mail** • info@intermec.com

Copyright © 1998 Intermec Technologies Corporation. All rights reserved. All trademarks are the property of their respective owners. Contents subject to change. Printed in the U.S.A. 608566 9/98