

## Rice Lake MB Series Balances



MB-3000E

PART #	DESCRIPTION	PART #	DESCRIPTION
66742	..... 150g x 0.001g	66744	..... 600g x 0.01g
66741	..... 150g x 0.01g	66745	..... 1500g x 0.1g
66743	..... 300g x 0.01g	66746	..... 3000g x 0.1g
66756	..... 600g x 0.02g	66747	..... 6000g x 0.1g

The MB Series offers performance at an affordable price. Capacities range from 150g x .001g to 6000g x 0.1g. Its revolutionary tuning fork technology provides automatic tracking for superior accuracy under any condition. Requiring no warm-up period, the MB Series also provides quick display response—precise measurement takes less than two seconds.



### Applications

- Quality control
- Research laboratory

### Standard Features

- Liquid Crystal Display (LCD), 0.64" (16.5mm)
- Automatic zero tracking
- Measures in three units: g, ct and oz (or lb)
- Switchable between any two weight units.
- No warm-up period required after power-up
- Five year limited warranty

### Options/Accessories

- 42566 ..... 115 volt adapter
- 42168 ..... 230 volt adapter
- 42169 ..... Internal rechargeable battery with sleep mode
- 42175 ..... Bidirectional RS-232 interface
- 42179 ..... Glass breeze shield (round pan balance only)
- 42183 ..... Carrying case
- 42192 ..... Additional operating manual

## Rice Lake QB Series Balances



QB-620E



QB-6200E

PART #	DESCRIPTION	PART #	DESCRIPTION
66754	..... 300g x 0.01g	66751	..... 3000g x 0.1g
66755	..... 600g x 0.02g	66752	..... 3000g x 0.01g
66749	..... 620g x 0.01g	66753	..... 6200g x 0.1g
66750	..... 1500g x 0.1g		

Offering fast, stable, and trouble-free measurement of lightweight items, the QB Series uses durable tuning fork technology. Capacities range from 300g x 0.01g to 6kg x 0.1g.

Easy to operate, it uses only three keys to activate all balance functions such as straightweigh mode, counting mode and over/under checkweighing mode. The QB Series can display weight in 12 units, making it truly international and able to function anywhere.



### Applications

- Industrial environments
- Counting, checkweighing and formulating for industrial applications

### Standard Features

- Liquid Crystal Display (LCD), 0.5" (12.5mm)
- Automatic zero tracking
- Measures in 12 units: g, kg, ct, oz, lbs, ozt, dwt, gr, Taels and mommes
- Counting mode
- Checkweighing mode
- Switchable for straightweighing, piece count, over/under checkweighing modes
- No warm-up period required after power-up
- Five year limited warranty
- Dust Cover

### Options/Accessories

- 42566 ..... 115 volt adapter
- 42168 ..... 230 volt adapter
- 42171 ..... Internal rechargeable battery with sleep mode
- 42174 ..... Bidirectional RS-232 interface
- 42177 ..... Glass breeze shield
- 41555 ..... Limit output pack
- 42181 ..... Dust cover
- 42194 ..... Additional operating manual