SURVIVOR® FB Series Electronic Flexure Base Floor Scale







(SEE CHART ON BACK OF PAGE FOR PART #'S)

The SURVIVOR FB features a unique flexure design that transmits all force via stainless steel flexures. The load is transferred from the levers to the load cell by a wire rope assembly, resulting in greater stability, increased weighment accuracy and a base that is more resistant to shock-loads and vibration.

The FB base utilizes "through pivot head loading." This exclusive Rice Lake Weighing Systems feature loads the flexures for optimal signal sensitivity and places the load tubes well into the base corners to prevent deck tipping.

Setup can be accomplished in a matter of minutes by simply backing off six bolts and connecting the load cell cable to your meter. The SURVIVOR FB can be used with any Rice Lake Weighing Systems indicator.

Applications

- Industrial processing
- · Heavy-duty weighing
- · Pallet weighing
- · Shipping and receiving

Standard Features

- One S-type, double-plated load cell
- Rugged all-steel construction
- · Unique flexure design filters motion and shock loading
- Stainless steel flexures
- · NTEP certified

Options/Accessories

19352 Floor stand for indicator, suitable for IQ plus® 310A, IQ700, UMC444 & UMC555

16940 Additional operating manual

Fork Lift Skid with fixed pedestals:

18747 FBP48, 48" (1219.2mm) wide 18748 FBP60, 60" (1524.0mm) wide 18749 FBP72, 72" (1828.8mm) wide

18750 FBP84, 84" (2133.6mm) wide

Consult factory for additional options:

- · Hot dipped galvanized coating
- · Stainless steel construction
- · Stainless steel load cell
- · Special sizes, heights and capacities available upon request

Survivor FB Specifications

APPROVALS:

NTEP certified, CC# 91-138, Class III 5000d

ELECTRICAL:

EXCITATION: 10 VDC - 15 VDC max NONLINEARITY: .03% FS

NONLINEARITY: .03% FS HYSTERISES: .02% FS BRIDGE RESISTANCE: 350 ohms OUTPUT: 3.0 mV/V

LOAD CELL CONSTRUCTION:

High-alloy tool steel, double plated chrome over nickel

END LOADING CAPACITY:

100% of scale capacity

SAFE OVERLOAD CAPACITY:

150% of scale capacity

WARRANTY:

Two year limited warranty

DIMENSIONS

FXB BASES	PART #		PACITY (KG)	L x W x H Inches	SHIP WT LB
			` '	24" x 24" x 7.25"	
			٠ 5/	24" x 24" x 7.25"	
			. 0.	30" x 30" x 7.25"	
				30" x 30" x 8.25"	
FB3030-5000				30" x 30" x 8.00"	
* FB3636-3000	18698	3000 lb		36" x 36" x 8.25"	
FB4848-3000	18732	3000 lb	(1500 kg)	48" x 48" x 8.00"	740 lb
* FB4848-5000	18699	5000 lb	(2500 kg)	48" x 48" x 8.00"	740 lb
* FB4848-10,000	18700	10,000 lb	(5000 kg)	48" x 48" x 10.00"	770 lb
* FB4848-20,000	18701	20,000 lb	(10,000 kg)	48" x 48" x 13.50"	1175 lb
* FB4860-5000	18702	5000 lb	(2500 kg)	48" x 60" x 10.00"	850 lb
* FB4860-10,000	18703	10,000 lb	(5000 kg)	48" x 60" x 10.00"	888 lb
* FB4860-20,000	18704	20,000 lb	(10,000 kg)	48" x 60" x 13.50"	1300 lb
* FB4872-5000	18705	5000 lb	(2500 kg)	48" x 72" x 11.25"	1275 lb
				48" x 72" x 11.25"	
* FB6060-5000	18708	5000 lb	(2500 kg)	60" x 60" x 10.00"	1025 lb
* FB6060-10,000	18709	10,000 lb	(5000 kg)	60" x 60" x 10.00"	1045 lb
				60" x 60" x 13.50"	1400 lb
* FB6072-20,000	18712	20,000 lb	(10,000 kg)	60" x 72" x 13.50"	1575 lb
				60" x 84" x 11.25"	
* FB6084-20,000	18714	20,000 lb	(10,000 kg)	60" x 84" x 13.50"	1850 lb
FB7272-30,000	18717	30,000 lb	(15,000 kg)	72" x 72" x 17.75"	2000 lb
				84" x 84" x 15.50"	
FB96120-30,000	18727	30,000 lb	(15,000 kg)	96" x 120" x 19.75"	4700 lb

^{*} NTEP certified

FORK LIFT SKID WITH FIXED PEDESTALS

TOTAL ELL TOTAL WITH TIMED I EDECTIVES							
	WIDTH	SHIP WT					
PART #	IN (MM)	LB (KG)					
18747 48"	(1219.2mm)	52 lb (23.6 kg)					
18748 60"	(1524.0mm)	64 lb (29.1 kg)					
18749 72"	(1828.8mm)	75 lb (34.1 kg)					
18750 84"	(2133.6mm)	86 lb (39.0 kg)					