




BLF Single-Ended Beam, Stainless Steel



RATED CAPACITY	DIMENSIONS										
	A	B	C	D	E	F	G	H	J	K	M
lb/inches											
1500-2500	9.00	6.00	.62	1.75	.59	.53	.69	.56	5/8-18 UNF	.31	1.13
5000	10.00	6.25	.75	2.00	.84	.78	.94	.50	7/8-14 UNF	.50	1.44
kg/millimeters											
680.4-1134.0	228.6	152.4	15.8	44.5	14.9	13.5	17.5	14.2	5/8-18 UNF	7.9	28.7
2268.0	254.0	158.8	19.1	50.8	21.3	19.8	23.9	12.7	7/8-14 UNF	12.7	36.6

SPECIFICATIONS:

Full Scale Output:	2.0 mV/V	Hysteresis:	0.02% Full scale
Bridge Resistance:	1000 ohms, nominal	Insulation Resistance:	5000 megohms
Material/Finish:	Stainless steel	Seal Type:	Environmentally protected
Temperature:	Compensated range 15°F to 115°F/-9°C to 46°C	Cable Length:	15'/4.6m
Manufacturer		Cable Color Code:	Green ... + Excitation Black - Excitation White + Signal Red - Signal Yellow Shield
Model Number:	BLF-XX-15100	Warranty:	1 year
Safe Overload:	150% Full scale		
Rated Excitation:	10V DC (15V maximum)		
Nonlinearity:	0.03% Full scale		

BLF ORDER INFORMATION

Load Rating	Part #	Suggested List Price
1500 lb (680.4 kg)	21918	\$535.00
2500 lb (1134.0 kg)	17114	\$535.00
5000 lb (2268.0 kg)	21917	\$640.00

INTERCHANGEABLE PRODUCTS

Manufacturer	Model
Fairbanks®	3-53581-X, 3-52921-1

Fairbanks is a registered trademark of Fairbanks Scales

USA: 800-472-6703 • Canada/Mexico: 800-321-6703 • International: 715-234-9171

Prices & Specifications subject to change without notice