





240 Single-Point Fluid Damped Alloy Steel/Stainless Steel Casing NTEP 1:5000 Class III Single Cell



Available upon request

RATED CAPACITY	DIMENSIONS										
	D	H	H1	H2	L	L1	L3	T	W	W1	W2
kg/millimeters											
2-50	50 DIA.	115.0	21.0	2.0	220.0	200.0	58.5	1/4-20 UNC X 10 DP	80.0	40.0	25.0
lb/inches											
4.4-110.2	1.97 DIA.	4.53	.83	.08	8.66	7.87	2.30	1/4-20 UNC X 0.39 DP	3.15	1.57	.98

SPECIFICATIONS:

Full Scale Output:	2.0 mV/V	Total Error:	0.025% Full scale
Bridge Resistance:	350 ohms, nominal	Insulation Resistance:	5000 megohms
Material/Finish:	Anodized aluminum load cell in alloy steel or stainless steel enclosure	Seal Type:	Environmentally protected
Temperature:	Operating temperature range 32°F to 122°F/0°C to 50°C	Cable Length:	3m/10'
Manufacturer		Cable Color Code:	Green + Excitation
Model Number:	0240-XXXX-922 (Alloy) 0240-XXXX-923 (Stainless Steel)		Black - Excitation
Safe Overload:	150% at center loading point, full scale		Blue + Sense
Rated Excitation:	10V DC (15V maximum)		Brown ... - Sense
		Warranty:	Red + Signal
			White - Signal
			2 years

240 ORDER INFORMATION

Load Rating	Part #	Suggested List Price
Alloy Steel*		
*2 kg (4.4 lb)	17559	\$670.00
5 kg (11.0 lb)	17560	\$670.00
7 kg (15.4 lb)	17561	\$670.00
10 kg (22.0 lb)	17562	\$670.00
15 kg (33.1 lb)	17563	\$670.00
20 kg (44.1 lb)	17564	\$670.00
30 kg (66.1 lb)	17565	\$670.00
50 kg (110.2 lb)	17566	\$670.00
Stainless Steel*		
*2 kg (4.4 lb)	17567	\$795.00
5 kg (11.0 lb)	17568	\$795.00
7 kg (15.4 lb)	17569	\$795.00
10 kg (22.0 lb)	17570	\$795.00
15 kg (33.1 lb)	17571	\$795.00
20 kg (44.1 lb)	17572	\$795.00
30 kg (66.1 lb)	17573	\$795.00
50 kg (110.2 lb)	17574	\$795.00

* Non-NTEP models available; consult factory.

NOTE: The special fluid damped operation is particularly well suited for applications where quick weighment is required, e.g., checkweighers.

USA: 800-472-6703 • Canada/Mexico: 800-321-6703 • International: 715-234-9171