

IQ F - S E R I E S

FLIP DIGIT REMOTE DISPLAYS

SURVIVOR[®]

GROSS



RICE LAKE WEIGHING SYSTEMS
Industrial Solutions on a Global Scale[®]

SURVIVOR

IQ F - S E R I E S

FLIP DIGIT REMOTE DISPLAYS



SURVIVOR F60 shown with backlight option

A Remote Display that Likes to be Seen...

After all, that's really what it's all about. Whether it's driving rain, heavy snow, or blinding sunlight, the IQ F-Series remote displays provide bright, bold, easy-to-view weight readings that'll keep your operation moving.

The IQ F-Series' unparalleled design offers NEMA 4 enclosures that take waterproofing technology to a new extreme. State-of-the-art sealing, a sloped surface for runoff, and attention to details—like rubber-backed washers—add up to a unit that's built to withstand nature's harshest elements. Simply speaking—they're ready to work when you are.

Advanced RS-232 and 20 mA current loop interfaces allow for compatibility with almost any system, and produce fast, accurate weight, time and temperature readings.

The IQ F-Series utilizes a unique AutoLink™ software feature that removes any guesswork from the installation. Plug in the communications cable between the digital indicator and remote display, and let AutoLink™ do the rest!

Standard Features:

- Durable NEMA 4 waterproof enclosure
- AutoLink™ software for instant interfacing
- RS-232 and 20 mA current loop
- Serial output port for daisy-chaining
- Gross, net, lb, and kg annunciators
- 6 highly-visible yellow display digits
- Weigh mode selection
- Fixed decimal point
- Available in 1.5", 4", and 6" digit sizes

Options/Accessories:

- Time and temperature
- Fluorescent backlighting
- Visor. Available for F40 (4-inch) and F60 (6-inch)
- Wireless point-to-point transceiver




SURVIVOR F60 shown with optional visor

Specifications:

Display:	6 high-visibility fluorescent yellow 1.5", 4" or 6" digits (38.1, 101.6, and 152.4mm) 1.5-inch: 60 ft (18.2m) maximum viewing distance 4-inch: 160 ft (48.8m) maximum viewing distance 6-inch: 240 ft (73.2m) maximum viewing distance
Input Interface:	20 mA current loop (active/passive), RS-232, standard ASCII serial characters
Baud Rate:	300, 600, 1200, 2400, 4800, 9600, and 19200; AutoLink™, or DIP switch manual setting
Character Format:	7 odd, 7 even, 8 none, 1 or 2 stop bits; AutoLink™, or DIP switch manual setting
Update:	Continuous update or out-of-motion-only update
Power Consumption:	SURVIVOR IQ F15 (1.5-inch) 18 watts standard; 52 watts with backlight SURVIVOR IQ F40 (4-inch) 52 watts standard; 75 watts with backlight SURVIVOR IQ F60 (6-inch) 75 watts standard; 115 watts with backlight
Line Voltages:	115 or 230 VAC
Time Option:	DIP switch selectable ON/OFF or 12 hour/24 hour, external set switch, 12 and 24 hour format
Temperature Option:	DIP switch selectable ON/OFF, displays °C and °F
Weight:	14.5 lb (6.6 kg) SURVIVOR IQ F15 44.1 lb (20.0 kg) SURVIVOR IQ F40 69.4 lb (31.5 kg) SURVIVOR IQ F60
Enclosure:	All-steel NEMA 4 enclosure for 4" and 6" models FRP enclosure on 1.5" model
Warranty:	One year limited warranty

Dimensions:



Your Rice Lake Weighing Systems Distributor is:

RICE LAKE WEIGHING SYSTEMS

Industrial Solutions on a Global Scale®

230 W. Coleman St. • Rice Lake, WI 54868 • USA

TEL: 715-234-9171 • FAX: 715-234-6967 • WEB SITE: <http://www.rlws.com>

© Rice Lake Weighing Systems 1998 PN 44971 3/98
Specifications subject to change without notice

