

Applications

- Asset tracking
- Document management
- Inventory control
- Shipping/receiving
- Work in process
- Ticketing

Standard Features

- 203 dpi print resolution (8 dots/mm)
- 10" (254mm) per second
- 1MB standard RAM
- Parallel and serial Interface
- Zebra's E³ printhead energy control
- Windows®-based driver
- 32-bit RISC microprocessor
- No Tools Required for changing printhead
- Transmissive and reflective media sensing
- Operator controls via front panel buttons and LEDs, configuration Settings via DIP switches and software
- Die-cast aluminum frame: 0.20" (5mm) thick
- Clear window on media cover: easy to view supplies, ribbon & labels



PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
46779	Z4000 Direct Thermal/Thermal Transfer Printer w/RS-232/422/485 & parallel interface, 115 VAC	25 lb	\$1,995.00
48029	Z4000 Direct Thermal/Thermal Transfer Printer w/RS-232/422/485 & parallel interface, 230 VAC	25 lb	1,995.00
OPTIONS/ACCESSORIES			
46817	Cutter with catch tray (field installable)		700.00
46801	Deluxe front panel with LCD (field installable)		200.00
46816	Value peel option (field installable)		100.00
46812	Rewind/peel combo (field installable)		500.00
46819	300 dpi printhead (field installable)		700.00
64786	Wireless transmitter receiver for printers, 2.46 GHz, includes RS-232 cable, power supply & software (requires a set of two or more)		495.00
48411	Operators manual		25.00
CABLES			
15552	Custom RS-232 cable		95.00
41501	6' serial cable (DB25 to DB25)		49.00
37527	6' parallel cable		29.00

Consult factory for other available options

ZEBRA Z4000 SPECIFICATIONS

PRINT CHARACTERISTICS

Print Speed: 10" (254mm) per second standard, 6" (152mm) per second optional
Resolution: 203 dpi (8 dots/mm), 300 dpi (12 dot/mm) optional
Print Width: 4.1" (118mm)
Print Length:
 203 dpi: 37" (940mm) standard, 136" (3454mm) optional
 300 dpi: 16" (406mm) standard, 61" (1549mm) optional

RIBBON

0.94" to 4.33" (24 to 110mm) on 1.0" (25.4mm) I.D. core to 3.2" (81.3mm) maximum O.D.

MEDIA

Media Thickness: 0.0023" to 0.009" (0.058 to 0.23mm)
Media Width: 0.50 to 4.5" (12-110mm)
Supply Roll Capacity: 8" (203mm) O.D., 3" (76mm) I.D., Maximum Length: 37" (940mm) standard, 39" (990.6mm) optional with 203 dpi; 16" (406mm) standard, 39" (990.6mm) optional with 300 dpi

BAR CODES

Codes: Code 11, Code 39, Code 93, Code 128, ISTB 128, UPC-A, UPC-E, EAN-8, EAN-13, Postnet, EAN and UPC with two- or five-digit supplements, Interleaved 2 of 5, Standard 2 of 5, Industrial 2 of 5, LOGMARS, MSI, Plessey, CODABLOCK, PDF-417, Code 49, MaxiCode Datamatrix, Ultracode

INTERFACING

RS-232/422/485 serial ports & IEEE 1284 bidirectional parallel port can both be used at the same time

ELECTRICAL

Operating Voltage: 115, 230 VAC, 50/60 Hz

APPROVALS

UL, CSA and carries CE mark of compliance

WARRANTY

One year limited warranty on parts, 6 months on printhead.

DISTRIBUTORS CAN ORDER ONLINE :

www.rlws.com