



LP-2022 & LP-2042



Applications

- Tracking resources and shipments
- Point-of-sale
- Medical field labeling and tracking patient files and specimens

Standard Features

- Low-cost direct thermal label printers
- 128K memory standard
- (LP-2022) Print width 2.20", 2" (50.8mm) per second print speed, 203 dots per inch
- (LP-2042) Print width 4.09", 2 LPS print speed, 203 dpi
- Serial or parallel interface

PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
37004	LP2022SA - Printer w/serial interface, 115 VAC	10 lb	\$395.00
40394	LP2022SE - Printer w/serial interface, 230 VAC	10 lb	420.00
37003	LP2022SAT - Printer w/serial interface & label peeler, 115 VAC	10 lb	439.00
40395	LP2022SET - Printer w/serial interface & label peeler, 230 VAC	10 lb	465.00
37006	LP2022PA - Printer w/parallel interface, 115 VAC	10 lb	395.00
40396	LP2022PE - Printer w/parallel interface, 230 VAC	10 lb	420.00
37005	LP2022PAT - Printer w/parallel interface & label peeler, 115 VAC	10 lb	439.00
40397	LP2022PET - Printer w/parallel interface & label peeler, 230 VAC	10 lb	465.00
37012	LP2042PSA - Printer w/serial & parallel interface, 115 VAC	10 lb	495.00
40399	LP2042PSE - Printer w/serial & parallel interface, 230 VAC	10 lb	525.00
37013	LP2042PSAT - Printer w/serial & parallel interface & label peeler, 115 VAC	10 lb	539.00
40400	LP2042PSET - Printer w/serial & parallel interface & label peeler, 230 VAC	10 lb	570.00
OPTIONS/ACCESSORIES			
37149	RW1 power rewinder		395.00
37148	TAB1 IBM Twinax protocol adapter box		550.00
37147	5" capacity label roll holder		110.00
36993	7" capacity label roll holder		110.00
38794	Cleaning Cards 2x6, 25/Box		30.00
38795	Cleaning Cards 4x6, 25/Box		30.00
64786	Wireless transmitter receiver for printers, 2.46 GHz, includes RS-232 cable, power supply & software (requires a set of two or more)		495.00
CABLES			
15552	Custom RS-232 cable		95.00
37526	6' serial cable (DB9 to DB25)		29.00
37528	6' serial cable (DB9 to DB9)		29.00
37527	6' parallel cable		29.00

Consult factory for other available options

ELTRON LP-2022/2042 SPECIFICATIONS

PRINT CHARACTERISTICS

Print Speed: 1.5" to 2" (38 to 51mm) per second**Resolution:** 203 dpi (8 dots/mm)**Print Width:**

LP-2022: 2.20" (56mm)

LP-2042: 4.09" (104mm)

Print Length: Unlimited (line mode)**MEDIA****Maximum Media Width:**

LP-2022: 2.36" (60mm)

LP-2042: 4.25" (108mm)

Supply Roll Capacity: 1.39" (35.3mm) max. O.D. on

a 0.5" (12.5mm) I.D. core

BAR CODES**Codes:** Code 39, Code 93, Code 128, B & C, Codabar, Interleaved 2 of 5, UPC-A, UPC-E, EAN-13, EAN-8, POSTNET**INTERFACING**

LP-2022: Centronics® parallel or RS-232 serial

LP-2042: Centronics® parallel and RS-232 serial

Note: 9600, 8 databits, 1 stop, no parity only

ELECTRICAL**Operating Voltage:** 115, 230 VAC, 50/60 Hz**APPROVALS**

UL, CSA, TUV-GS, complies with FCC Class A and VDE Class B

WARRANTY

One year limited warranty on parts, 90 days or 500,000 linear inches on printhead.