

Applications

- Shipping & receiving
- Shelf labeling
- Counting scales

Standard Features

- 512KB flash memory, 128KB image buffer memory
- CAL Tools software
- Windows® printer driver
- Roll capacity: 5"

LP/TLP-2722:

- Print width 2" (50.8mm) per second print speed, 203 dpi
- Serial or parallel interface

LP/TLP-2742:

- Print width 4.09", 2" (50.8mm) per second print speed, 203 dpi
- Serial and parallel interface



LP/TLP-2722



LP/TLP-2742

LP/TLP-2722 &
LP/TLP-2742



PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
LP-2722 (2" SERIES)			
53120	LP2722SA - LP-2722 Direct Thermal Printer, serial interface, 115 VAC	6 lb	\$545.00
53121	LP2722PA - LP-2722 Direct Thermal Printer, parallel interface, 115 VAC	6 lb	545.00
53124	LP2722SE - LP-2722 Direct Thermal Printer, serial interface, 230 VAC	6 lb	579.00
53125	LP2722PE - LP-2722 Direct Thermal Printer, parallel interface, 230 VAC	6 lb	579.00
53128	LP2722SAC - LP-2722 Direct Thermal Printer, serial interface w/cutttter, 115 VAC	7 lb	845.00
53129	LP2722PAC - LP-2722 Direct Thermal Printer, parallel interface w/cutter, 115 VAC	7 lb	845.00
53132	LP2722SEC - LP-2722 Direct Thermal Printer, serial interface w/cutter, 230 VAC	7 lb	890.00
53133	LP2722PEC - LP-2722 Direct Thermal Printer, parallel interface w/cutter, 230 VAC	7 lb	890.00
64810	LP2722PAT - LP-2722 Direct Thermal Printer, parallel interface w/label peeler, 115 VAC	6 lb	575.00
64811	LP2722SAT - LP-2722 Direct Thermal Printer, serial interface w/label peeler, 115 VAC	6 lb	575.00
64812	LP2722PET - LP-2722 Direct Thermal Printer, parallel interface w/label peeler, 230 VAC	6 lb	609.00
64813	LP2722SET - LP-2722 Direct Thermal Printer, parallel interface w/label peeler, 230 VAC	6 lb	609.00
TLP-2722 (2" SERIES)			
53122	TLP2722SA - TLP-2722 Direct Thermal/Thermal Transfer Printer, serial interface, 115 VAC	6 lb	645.00
53123	TLP2722PA - TLP-2722 Direct Thermal/Thermal Transfer Printer, parallel interface, 115 VAC	6 lb	645.00
53126	TLP2722SE - TLP-2722 Direct Thermal/Thermal Transfer Printer, serial interface, 230 VAC	6 lb	685.00
53127	TLP2722PE - TLP-2722 Direct Thermal/Thermal Transfer Printer, parallel interface, 230 VAC	6 lb	685.00
53130	TLP2722SAC - TLP-2722 Direct Thermal Printer, serial interface w/cutttter, 115 VAC	7 lb	945.00
53131	TLP2722PAC - TLP-2722 Direct Thermal Printer, parallel interface w/cutter, 115 VAC	7 lb	945.00
53134	TLP2722SEC - TLP-2722 Direct Thermal Printer, serial interface w/cutter, 230 VAC	7 lb	990.00
53135	TLP2722PEC - TLP-2722 Direct Thermal Printer, parallel interface w/cutter, 230 VAC	7 lb	990.00
64814	TLP2722PAT - TLP-2722 Direct Thermal Printer, parallel interface w/label peeler, 115 VAC	6 lb	679.00
64815	TLP2722SAT - TLP-2722 Direct Thermal Printer, serial interface w/label peeler, 115 VAC	6 lb	679.00
64816	TLP2722PET - TLP-2722 Direct Thermal Printer, parallel interface w/label peeler, 230 VAC	6 lb	721.00
64817	TLP2722SET - TLP-2722 Direct Thermal Printer, parallel interface w/label peeler, 230 VAC	6 lb	721.00
LP-2742 (4" SERIES)			
53136	LP2742PSA - LP-2742 Direct Thermal Printer, serial/parallel interface, 115 VAC	8 lb	575.00
53138	LP2742PSE - LP-2742 Direct Thermal Printer, serial/parallel interface, 230 VAC	8 lb	610.00
53140	LP2742PSAC - LP-2742 Direct Thermal Printer, serial/parallel interface w/cutter, 115 VAC	9 lb	875.00
53142	LP2742PSEC - LP-2742 Direct Thermal Printer, serial/parallel interface w/cutter, 230 VAC	9 lb	920.00
62990	LP2742PSAT - LP-2742 Direct Thermal Printer, serial/parallel interface w/label peeler, 115 VAC	8 lb	610.00
53140	LP2742PSET - LP-2742 Direct Thermal Printer, serial/parallel interface w/label Peeler, 230 VAC	8 lb	610.00
TLP-2742 (4" SERIES)			
53137	TLP2742PSA - TLP-2742 Direct Thermal/Thermal Transfer Printer, serial/parallel interface, 115 VAC	8 lb	675.00
53139	TLP2742PSE - TLP-2742 Direct Thermal/Thermal Transfer Printer, serial/parallel interface, 230 VAC	8 lb	710.00
53141	TLP2742PSAC - TLP-2742 Direct Thermal/Thermal Transfer Printer, serial/parallel interface w/cutter, 115 VAC,	9 lb	975.00
53143	TLP2742PSEC - TLP-2742 Direct Thermal/Thermal Transfer Printer, serial/parallel interface w/cutter, 230 VAC	9 lb	1,020.00
62991	TLP2742PSAT - TLP-2742 Direct Thermal/Thermal Transfer Printer, serial/parallel interface w/label peeler, 115 VAC	8 lb	710.00
62993	TLP2742PSET - TLP-2742 Direct Thermal/Thermal Transfer Printer, serial/parallel interface w/label peeler, 230 VAC	8 lb	710.00
OPTIONS/ACCESSORIES			
36988	Keyboard display unit		256.00
38812	Time and date		39.00
37149	RW1 power rewinder		395.00
37148	TAB1 IBM Twinax protocol adapter box		550.00
36992	CAL 3 software		195.00
64786	Wireless transmitter receiver for printers, 2.46 GHz, includes RS-232 cable, power supply & software (requires a set of two or more)		495.00
38941	Cleaning Pen for open printhead printers		15.00
38794	Cleaning cards 2x6, 25 per box		30.00
38795	Cleaning cards 4x6, 25 per box		30.00
CABLES			
15552	Custom RS-232 cable		95.00
37526	6' serial cable (DB9 to DB25)		29.00
37528	6' serial cable (DB9 to DB9)		29.00
37527	6' parallel cable		29.00

See next page for specifications

PRINTERS

DIRECT THERMAL/
THERMAL
TRANSFER

Eltron® LP/TLP-2722 & LP/TLP-2742 (Cont.)

ELTRON LP/TLP 2722 & 2742 SPECIFICATIONS

PRINT CHARACTERISTICS

Maximum Print Speed:
2" (51mm) per second
Resolution:
203 dpi (8 dots/mm)
Maximum Print Width:
LP/TLP-2722: 2.12" (54mm)
LP/TLP-2742: 4.09" (104mm)
Print Length: 0.38" to 11" (9.7 to 279mm)

MEDIA SPECIFICATIONS

Maximum Media Width:
LP/TLP-2722: 2.36" (60mm)
LP/TLP-2742: 4.65" (118mm)
Maximum Media Diameter: 5.0" (127mm)

RIBBON

Ribbon Types (TLP only): Wax, wax/resin, resin

Ribbon Width:

LP/TLP-2722: 1.3" (33mm), 2.24" (56.9mm)
LP/TLP-2742: 1.3" (33mm), 2.25" (64mm),
3.3" (84mm), 4.3" (109mm)

Ribbon Length:

3600' (91m)

Ribbon Core Diameter: 0.5" (12.5mm)

BAR CODES

Codes: Code 39, IExtended Code 39, Code 93, Code 128 UCC, Code 128 Autoselect, Codabar, Interleaved 2 of 5, UPC-A, UPC-E, 2 and 5 digit add-on, UPC Shipping container code, EAN-8, EAN-13, 2 and 5 digit add-on, UCC-EAN-128, POSTNET, German Postal Code, MaxiCode, PDF-417/Macro PDF

MEMORY

LP/TLP-2722: SRAM: 128K/256K, Flash: 512K/1MB
LP/TLP-2742: SRAM: 256K/512K, Flash: 512K/1MB

INTERFACING

Centronics® Parallel port or RS-232 serial

ELECTRICAL

115 VAC 60 Hz or 230 VAC 50 Hz

APPROVALS

Meets UL, CUL, TUV requirements, complies with FCC Class A, CE mark (international models only)

WARRANTY

One year limited warranty on parts. One year or 1 million linear inches on original printhead. 90 days on replacement printhead.

Eltron® TLP-3742 Direct Thermal/Thermal Transfer Printer



Applications

- Electronic component labeling
- Small labels with high-resolution requirements
- Pharmacuticle labeling
-

Standard Features

- 512K memory standard
- Serial and parallel interface
- Eltron Common Architecture Program (ECAP)
- Roll capacity: 5"
- Print width: 4.09" (104mm), 2" (50.8mm) per second print speed, 300 dpi (11.8 dots/mm)
- Label guide adjustment
- Small footprint
- Clear media cover to easily monitor media supply levels

PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
63000	TLP-3742PSA - TLP-3742 Direct Thermal/Thermal Transfer Printer, 115 VAC	7 lb	\$845.00
63001	TLP-3742PSAT - TLP-3742 Direct Thermal/Thermal Transfer Printer, 115 VAC	7 lb	880.00
63002	TLP-3742PSE - TLP-3742 Direct Thermal/Thermal Transfer Printer, 230 VAC	7 lb	845.00
63003	TLP-3742PSET - TLP-3742 Direct Thermal/Thermal Transfer Printer, 230 VAC	7 lb	880.00
OPTIONS/ACCESSORIES			
37149	Desktop power rewinder, 115 VAC		395.00
38812	Time and date		39.00
36992	Create-A-Label 3 software for Windows®		195.00
41491	Create-A-Label 3 Tools software for Windows®		25.00
37143	Windows print drivers		25.00
36988	Keyboard display unit		256.00
40821	Battery pack kit		285.00
64961	Eltron print server		349.00
64786	Wireless transmitter receiver for printers, 2.46 GHz, includes RS-232 cable, power supply & software (requires a set of two or more)		495.00
CABLES			
37527	6' parallel interface cable		29.00
37528	6' serial interface cable (DB9 to DB9)		29.00
37526	6' serial interface cable (DB25 to DB9)		29.00

ELTRON TLP-3742 SPECIFICATIONS

PRINT CHARACTERISTICS

Maximum Print Speed:
2" (51mm) per second
Resolution:
300 dpi (12 dots/mm)
Maximum Print Width:
4.09" (104mm)
Print Length: 0.38" to 10" (9.7 to 254mm)
Character Set: Modified IBM® Code Page 850; includes characters for English and most European, Scandinavian and Spanish speaking countries
Font Expansion/Rotation: All fonts expandable vertically and horizontally up to 24x; fonts and graphics can be printed in four directions: 0°, 90°, 180°, & 270°
Graphics: Lines, boxes & graphics

MEDIA SPECIFICATIONS

Maximum Media Width:
4.65" (118mm)
Maximum Media Diameter: 5.0" (127mm)

RIBBON

Wax, wax/resin, resin

Ribbon Width:

1.3" (33mm), 2.5" (64mm), 3.3" (84mm), 4.3" (109mm)

Ribbon Length:

3600' (91m)

Ribbon Core Diameter: 0.5" (12.5mm)

BAR CODES

Codes: Code 39, IExtended Code 39, Code 93, Code 128 UCC, Code 128 Autoselect, Codabar, Interleaved 2 of 5, UPC-A, UPC-E, 2 and 5 digit add-on, UPC Shipping container code, EAN-8, EAN-13, 2 and 5 digit add-on, UCC-EAN-128, POSTNET, German Postal Code, MaxiCode, PDF-417/Macro PDF

MEMORY

SRAM: 512K/Upgrade 1MB

FLASH: 1MB

INTERFACING

Centronics® Parallel port or RS-232 serial

ELECTRICAL

115/230 VAC, 60/50 Hz

APPROVALS

UL, CUL, FCC Class A, CE mark

WARRANTY

One year limited warranty on parts. One year or 1,000,000 linear inches on original printhead. 90 days on replacement printhead.