

Eltron® TLP-2746 Direct Thermal/Thermal Transfer Printer**NEW!**
Product**Applications**

- Industrial label printing
- Shipping & receiving
- Inventory/box labeling

Standard Features

- 16-bit dual processors for faster throughput
- Serial and parallel interface
- Metal enclosure
- Flash memory & firmware
- 512 SRAM to print longer labels
- Create-A-Label Tools software
- Windows® printer driver
- Flexible media support
- Print width 4" (101.6mm)
- 2" (50.8mm), 4" (101.6mm), and 6" (152.4mm) per second print speed, 203 dpi
- EPL2 programming language

PART # DESCRIPTION**EST. SHIP
WEIGHT****SUGGESTED
LIST PRICE**

63004	TLP2746PSAT - TLP-2746 Printer, 115 VAC	40 lb	\$1,495.00
63005	TLP2746PSAT - TLP-2746 Printer, 230 VAC	40 lb	1,495.00

OPTIONS/ACCESSORIES

36995	Automatic label & tag cutter	695.00
36996	Label & tag catcher (used with automatic cutter option)	110.00
36988	Keyboard display unit	256.00
38812	Time and date	39.00
41491	Create-A-Label Tools software	25.00
36992	Create-A-Label Professional for Windows®	195.00
37143	Windows printer drivers	25.00
64786	Wireless transmitter receiver for printers, 2.46 GHz, includes RS-232 cable, power supply & software (requires a set of two or more)	495.00

CABLES

15552	Custom RS-232 cable	95.00
41276	9-pin to blunt end	49.00
37526	6' serial cable (DB9 to DB25)	29.00
37528	6' serial cable (DB9 to DB9)	29.00
37527	6' parallel cable	29.00

Consult factory for other available options

ELTRON TLP-2746 SPECIFICATIONS**PRINT CHARACTERISTICS****Print Speed:** 2" (50.8mm), 4" (101.6mm), &

6" (152.4mm) per second

Resolution: 203 dpi (8 dots/mm)**Print Width:** 4" (101.6mm)**Maximum Print Length:** 11" (279.4mm)**MEDIA****Media Width:** 1" (25.4mm) minimum; 4.25" (108mm) maximum**Supply Roll Capacity:** 8" (203.2mm) with 1" I.D. minimum**RIBBON**

Wax, wax/resin, resin

Ribbon Core Diameter: 1" (25.4mm) I.D. Core**Ribbon Widths:** 1.3" (33mm), 2.5" (64mm), 3.3" (84mm), & 4.3" (109mm)**Ribbon Length:** 14,270' (362m)**BAR CODES****Codes:** Code 39, Extended Code 39, Code 93, Code 128 UCC, Code 128 Autoselect, Codabar, interleaved 2 of 5, UPC-A, UPC-E, 2 and 5 digit add-on, UPC shipping container code, EAN-8, EAN-13, 2 and 5 digit add-on, UCC/EAN-128, Postnet, German Postal Code, MaxiCode, PDF-417/Macro PDF, QR Code**INTERFACING**

Centronics® Parallel port or RS-232 serial

MEMORY**SRAM:** 512K maximum**Flash:** 1 MB maximum**ELECTRICAL**

Operating Voltage: 115, 230 VAC, 50/60 Hz

APPROVALS

UL, CUL, FCC Class A, CE mark

WARRANTY

One year limited warranty on parts, 90 days or 500,000 linear inches on printhead.