

Applications

- Shipping and receiving labeling
- Retail UPC and EAN labeling
- Inventory and laboratory specimen labeling

Standard Features

- 256K memory standard
- Serial and parallel interface
- Create-A-Label Tools software
- Windows® printer driver
- Roll capacity: 5"
- Print width: 4" (101mm), 2.5" (63.5mm) per second print speed, 203 dpi



PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
46247	Orion PSA - Direct Thermal Printer w/serial & parallel Interface, 115 VAC	3 lb	\$595.00
46246	Orion PSAT - Direct Thermal Printer w/serial & parallel Interface & label peeler, 115 VAC	3 lb	630.00
46249	Orion PSE - Direct Thermal Printer w/serial & parallel Interface, 230 VAC	3 lb	630.00
46248	Orion PSET - Direct Thermal Printer w/serial & parallel Interface & label peeler, 230 VAC	3 lb	665.00
OPTIONS/ACCESSORIES			
36988	Keyboard display unit		256.00
37149	RW1 power rewinder		395.00
41491	Create-A-Label 3 software for Windows®		25.00
36992	Create-A-Label Professional for Windows®		195.00
37143	Windows® printer drivers		25.00
38941	Cleaning pen for open printhead printers		15.00
38794	Cleaning cards 2x6, 25/Box		30.00
38795	Cleaning cards 4x6, 25/Box		30.00
64786	Wireless transmitter receiver for printers, 2.46 GHz, includes RS-232 cable, power supply & software (requires a set of two or more)		495.00
CABLES			
15552	Custom RS-232 cable		95.00
37526	6' serial cable (DB9 to DB25)		29.00
37528	6' serial cable (DB9 to DB9)		29.00
37527	6' parallel cable		29.00

Consult factory for other available options

ELTRON ORION SPECIFICATIONS

PRINT CHARACTERISTICS

Print Speed: 1" to 2.5" (25.4 to 63.5mm) per second
Resolution: 203 dpi (8 dots/mm)
Print Width: 4" (104mm)
Print Length: 11" (279mm) maximum, 0.5" (13mm) minimum, 22" (559mm) with expanded memory

MEDIA

Media Thickness: 0.003" (0.08mm) minimum, 0.007" (0.18mm) maximum
Media Width: 1" (25.4mm) minimum, 4.25" (108mm) maximum, 2.25" (57mm) for tag stock
Supply Roll Capacity: 5" (127mm) O.D. on a 1" (25mm), 1.25" (32mm), or 1.75" (45mm) core

BAR CODES

Codes: Code 39, Code 913, Code 128 UCC (Shipping Container Code), EAN 128, Code 128 (subsets A, B, and C), Codabar, Interleaved 2 of 5, UPC-A, UPC-E, 2 & 5 digit add-on, EAN-8, EAN-13, 2 & 5 digit add-on, POSTNET, German Postal Code, MaxiCode, PDF-17

INTERFACING

RS-232, XON/XOFF, OFF, DTR/DSR, Parallel (Centronics® Type 36 pin connector)

ELECTRICAL

Operating Voltage: 115, 230 VAC, 50/60 Hz

APPROVALS

UL, CUL, TUV, complies with FCC Class A and CE (International models only) standards

WARRANTY

One year limited warranty on parts, 90 days or 500,000 linear inches on printhead.