

NEW!
Product

Applications

- Pallet labeling
- Shipping & receiving
- Warehouse management
- Chemical and drum
- Work-in-progress
- Document management

Standard Features

- 512K Flash and 512K SRAM
- Print Speed: 4" (102mm) per second
- Maximum print width: 8.5" (216mm)
- Easy media loading
- 203 dpi (8 dots/mm) print resolution
- Batch or on-demand printing
- Industrial steel enclosure
- Prints text, graphics & bar codes in four directions: 0°, 90°, 80°, & 270°
- CAL tools software

PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
51039	Strata LP Direct Thermal, 115 VAC	18 lb	\$2,795.00
51040	Strata LP Direct Thermal w/label peeler, 115 VAC	18 lb	2,945.00
51050	Strata LP Direct Thermal, 230 VAC	18 lb	2,895.00
51051	Strata LP Direct Thermal w/label peeler, 230 VAC	18 lb	3,045.00
51041	Strata TLP Thermal Transfer/Direct Thermal, 115 VAC	18 lb	2,995.00
51049	Strata TLP Thermal Transfer/Direct Thermal w/label peeler, 115 VAC	18 lb	3,145.00
51053	Strata TLP Thermal Transfer/Direct Thermal w/label peeler, 115 VAC	18 lb	3,245.00
51052	Strata TLP Thermal Transfer/Direct Thermal, 230 VAC	18 lb	3,095.00
OPTIONS			
46455	512K Additional Flash memory (1MB total)		40.00
41491	Create-A-Label 3 software for Windows®		25.00
36992	Create-A-Label Professional for Windows®		195.00
37143	Windows® printer drivers		25.00
36988	Keyboard display unit		256.00
37148	IBM Twiax to EPL2 protocol converter interface, 115 VAC		550.00
CABLES			
37528	6' serial cable (DB9 to DB9)		29.00
37527	6' parallel cable		29.00

Consult factory for other available options

ELTRON STRATA LP/TLP SPECIFICATIONS

PRINT CHARACTERISTICS

Print Speed: 4" (101.6mm) per second
Resolution: 203 dpi (8 dots/mm)
Maximum Print Width: 8.5" (216mm)
Print Length: 11.0" (279mm) standard; up to 17" (431mm) print length with 384KB

RIBBON

Industry-standard ribbon core: 1.0" (25mm)

MEDIA

Media Width: 4.0" (100mm) minimum; 8.75" (222mm) maximum
Label Length: 0.50" (13mm) minimum; 11" (279mm) maximum

Supply Roll Capacity: 5.0" (127mm) maximum**Media Thickness:** 0.003" to 0.010" (0.076 to 0.254mm)**Media Sensing:** Gap, black line**BAR CODES**

Codes: Code 39, Code 128 (subset A, B and C), UCC/EAN-128, Code 93, Codabar, Interleaved 2 of 5, UPC-A, UPC-E, UPC-A (2 and 5 add-on), UPC-B (2 and 5 add-on), EAN13, EAN8, EAN13 2 and 5 add-on, EAN8, EAN13 (2 and 5 add-on), EAN8 (2 and 5 add-on), MaxiCode, Postnet, PDF417

INTERFACING

Centronics® Parallel port or RS-232 (DB9) serial

ELECTRICAL**Operating Voltage:** 115 - 60 Hz, 230 VAC - 50 Hz**APPROVALS**

UL, CUL, TUV, complies with FCC Class A and CE requirements

WARRANTY

One year limited warranty on parts, 90 days or 500,000 linear inches on printhead.