

Applications

- Parcel delivery labeling
- Shipping & receiving labeling
- Bin labels for parts
- Receipt printing for route accounting

Standard Features

- Serial interface
- 128K memory
- Shoulder strap and battery included
- Label peeler
- Create-A-Label Tools software
- Windows® printer driver
- Automatic battery save
- Overnight battery charger
- Print width: 4.09", 2" (50.8mm) per second print speed, 203 dpi



PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
37001	P2242 - Portable Direct Thermal Printer, 115 VAC	5 lb	\$895.00
40412	P2242 - Portable Direct Thermal Printer, 230 VAC	5 lb	895.00
OPTIONS/ACCESSORIES			
36997	BT1 NiCad battery pack		110.00
36998	BE1 12V battery eliminator		110.00
37000	CG1 2-slot fast charger, 115 VAC (2 Hour)		225.00
40393	CG1 2-slot fast charger, 230 VAC		225.00
36986	VH1 vehicle mount bracket		169.00
CABLES			
43916	Falcon to Printer Cable		40.00
<i>Consult factory for other available options</i>			

ELTRON TRANSPORT SPECIFICATIONS

PRINT CHARACTERISTICS

Print Speed: 1.5" & 2", (38.1 & 50.8mm) per second

Resolution: 203 dpi (8 dots/mm)

Print Width: 4.09" (104mm)

Print Length: 6.5" (165mm)

MEDIA

Media Thickness: 0.003" (.07mm) minimum; 0.008" (20mm) maximum

Media Width: 1.0" (25.4mm) minimum; 4.25" (108mm) maximum

Supply Roll Capacity: 2.1" (53mm) O.D. with 1" (25.4mm) O.D. core. Approximately 400' (10.2m) length of label material @ 7 mil media thickness

BAR CODES

Codes: Code 39, Code 93, Code 128 UCC (Shipping Container Code), Code 128 (subset A, B and C), Codabar, Ean 128, Interleaved 2 of 5, UPC-A, UPC-E, 2 & 5 digit add-on, EAN-8, EAN-13, 2 & 5 digit add-on, POSTNET, German Postal Code, Maxicode, PDF-417

INTERFACING

RS-232 (DB-9) with software switch rates of 1,200 to 19,200 baud, XON/XOFF, CTS/DTR

ELECTRICAL

Operating Voltage: 115, 230 VAC, 50/60 Hz

APPROVALS

UL, CUL, TUV, complies with FCC Class A and CE requirements

WARRANTY

One year limited warranty on parts, 90 days or 500,000 linear inches on printhead

Eltron® Low-cost Printer Accessories



KEYBOARD DISPLAY UNIT

- Designed for stand-alone applications
- Formats and user prompting commands stored in printer
- Serial port with DB9 interface

Retrieve stored forms and enter variable data via keyboard. The KDU features a two-line LCD that prompts for input and makes it easy to print labels in a stand-alone mode.



REWINDER

- Multiple label lengths
- Multiple label widths
- Range of inner and outer roll diameters

Create neat label rolls with a rewinder for your Eltron printer.



CUTTERS

- Label and tag stock cutting
- Label tray saves time and improves productivity
- Designed for most Eltron printers

Choose Eltron's high-quality, self-cleaning and sharpening tag and/or label liner cutters for your printer. Add a stacker and tray and keep your tags or labels neatly arranged.