


IDS-150A & 152 Ticket Printers **IDS-160** Tape PrinterIDS-150A & 152
Ticket Printers

IDS-160 Tape Printer

IDS-150A & 152 Ticket Printers
& IDS-160 Tape Printer**Applications**

- Truck scales
- Material handling
- Audit detail printing
- Production report printing

Standard Features

- Multicopy ticket printing
- Automatic document advance
- 4K character storage buffer
- Rugged sheet metal enclosure
- RS-232, 20 mA or RS-485 current loop serial interface

IDS-152 Additional Features:

- 30-character header label
- Transaction and station numbering
- Normal, enhanced or mixed print sizes
- Form sensor print inhibit
- Automatic: print wrap, line feed, paper release
- Time and date print format
- Bidirectional print
- Multi-strike print
- Left and top margin
- Inverted printing
- Eight operating modes

IDS-160:

- 30-character header label
- Transaction and station numbering
- Normal, enhanced or mixed print sizes
- Time and date format
- Form sensor print inhibit
- Axle weighing
- Automatic: print wrap, line feed, paper feed

PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
20150	IDS 150A Ticket Printer	18 lb	\$1,395.00
20136	IDS 152 Ticket Printer	18 lb	1,595.00
20158	IDS 160 Tape Printer	17 lb	1,595.00
OPTIONS/ACCESSORIES			
20496	One-ply paper roll, 3" W x 150' L		6.00
20497	Two-ply paper roll, 3" W x 150' L		8.00
IDS-150A			
34475	RS-232, 230 VAC Ticket Printer		1,395.00
20440	Ink ribbon, purple		6.00
20895	Time and Date		150.00
21221	Protective dust cover		55.00
22678	Additional operating manual		35.00
16803	Additional operating manual		35.00
IDS-152			
34476	230 VAC Ticket Printer		1,595.00
20440	Ink ribbon, purple		6.00
21221	Protective dust cover		55.00
16798	Additional operating manual		35.00
IDS-160			
34477	230 VAC Tape Printer		1,595.00
20447	Ink ribbon, purple		6.00
20544	Ink ribbon, black and red		6.00
16799	Additional operating manual		35.00
CABLES			
15567	25-pin 20 mA serial interface cable		49.00
15568	25-pin RS-232 serial interface cable		49.00
	<i>Interfaces to: IQ5000 and UMC2000 with simplex RS-232 or 6-pack multiple serial expansion board</i>		
15566	Blunt end, 20 mA/RS-232 serial interface cable		49.00
	<i>Interfaces to: UMC444, IQ plus 355, 390-DC, 590-DC, 510, 710, IQ600HB, IQ700HB, IQ plus 800/810, & IQ plus 310A</i>		
15565	Custom 20 mA/RS-232 serial interface cable		95.00
	<i>Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type. Standard cable length is 5 feet. \$2.00 charge for each additional foot.</i>		

IDS-150A, 152, & 160 Specifications**PRINT CHARACTERISTICS****Print Speed:**

IDS 150A: 1.25 lines per second

IDS 152: 3 lines per second

IDS 160: 2.4 lines per second

Characters Per Line:

IDS 150A/152: 40 wide, standard

IDS 160: 26 wide, standard

Print Line:

IDS 150A/152: 3.33" (84.6mm) wide

IDS 160: 2.16" (54.9mm) wide

Character Formation: 5 x 7 dot matrix**Character Height:**

IDS 150A: = 0.11" (2.8mm)

IDS 152/160: = 0.12" (3mm)

Character Width: 0.07" (1.8mm) wide (regular), 0.14" (3.6mm) wide (enhanced)**Character Set:** Full 96-character ASCII**Line Spacing:** 6 lines per inch (25.4mm)**RIBBON**

Inked spools, purple

INTERFACING**Serial Interfaces:** RS-232, 20 mA current loop or

RS-485 are all standard

Baud Rates: 300, to 9600**Parity:** Even, odd or none, user-selectable**Parallel Interface:** Optional**APPROVALS**

Built to UL and CUL safety standards

WARRANTY

One year limited warranty (includes printhead)