

Applications

- Truck scales
- Material handling
- Inventory control
- Retail sales transactions

Standard Features

- Double-strike high speed, 180 character per second (cps)
- Single copy or up to five-part multicopy forms
- Functions in slave capacity, printing information sent via RS-232 or weight extraction smart mode, processing information before printing
- Cash drawer kick-out function
- Inexpensive ink cartridge for no-mess ribbon changes
- Battery backup; optional time/date and consecutive number (or ID) are retained for a year or more in the event of a power failure



PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
34229	SP2200 Ticket Printer with RS-232 (black & light gray)	12 lb	\$1,195.00
34178	SP2200 Ticket Printer with RS-232 (light gray)	12 lb	1,195.00
40867	SP2200 Ticket Printer with RS-232 (blue & gray)	12 lb	1,195.00
35855	SP2200 Ticket Printer 230 VAC with RS-232 (black & light gray)	12 lb	1,195.00
35853	SP2200 Ticket Printer 230 VAC with RS-232 (light gray)	12 lb	1,195.00
40894	SP2200 Ticket Printer 230 VAC with RS-232 (blue & gray)	12 lb	1,195.00
OPTIONS/ACCESSORIES			
34228	SP2200 Ticket Printer with RS-232, time, date and switch module (black & light gray)		1,295.00
34227	SP2200 Ticket Printer with RS-232, time, date and switch module (light gray)		1,295.00
40868	SP2200 Ticket Printer with RS-232, time, date and switch module (blue & gray)		1,295.00
35856	SP2200 Ticket Printer 230 VAC with RS-232, time, date and switch module (black & light gray)		1,295.00
35854	SP2200 Ticket Printer 230 VAC with RS-232, time, date and switch module (light gray)		1,295.00
40895	SP2200 Ticket Printer 230 VAC with RS-232, time, date and switch module (blue & gray)		1,295.00
35231	Switch module		65.00
23170	Centronics® parallel interface adapter		65.00
20302	20 mA current loop		65.00
23169	RS-422		65.00
20308	Ink cartridge, black		22.00
22596	Ink cartridge, blue (minimum order 12)		26.00
21210	Protective dust cover		48.00
34282	Maintenance and service manual		25.00
34171	Additional operating manual		25.00
CABLES			
15548	25-pin 20 mA serial interface cable		49.00
15568	25-pin RS-232 serial interface cable		49.00
	<i>Interfaces to: IQ5000 and UMC2000 with simplex RS-232 or 6-pack multiple serial expansion board</i>		
15547	Blunt end, 20 mA/RS-232 serial interface cable		49.00
	<i>Interfaces to: UMC444, UMC555, IQ600HB, IQ700HB, IQ plus 800/810, IQ plus 310A, 355, 390-DC, 590-DC, 510, & 710</i>		
15565	Custom 20 mA/RS-232 serial interface cable		95.00
	<i>Custom cables are designed to interface with your specific equipment. Please specify equipment model number and connector type. Standard cable length is 5 feet. \$2.00 charge for each additional foot.</i>		

SP2200 Specifications

PRINT CHARACTERISTICS

Print Speed: 3.5 lines per second, 180 characters per second
Characters Per Line: 40 characters at 12 cpi
Print Area: 3.33" (84.6mm) wide
Character Formation: 5 x 9 dot matrix
Character Height: 0.1" (2.5mm) enhanced double-wide or 0.45 (11.4mm) on 4X. Can be inverted for left side of tickets
Character Set: Full 96-character ASCII (upper and lower case set)
Line Spacing: Six lines per inch (25.4mm)
Copies Printed: Single copy or up to five-part multicopy forms

PRINT MEDIA

Form thickness adjustable from 0.004" to 0.026" (0.1 to 0.7mm) by 0.004" step increments

RIBBON

Cartridge-type black or blue ink ribbon.
 Ribbon life is approximately 1 million standard characters

INTERFACING

Serial Interfaces: RS-232 standard; optional RS-422, 20 mA current loop or Centronics® Parallel
Baud Rates: 300, 600, 1200, 2400, 4800, 9600 or 19,200 selectable
Parity: 1 parity bit (even ignored by printer)

APPROVALS

Built to UL and CUL safety standards, CE mark, FCC approval pending

WARRANTY

One year limited warranty (includes printhead)