

Zebra® S400 & S600 Direct Thermal/Thermal Transfer Printers

NEW!
ProductS400 Direct Thermal/
Thermal Transfer PrinterS600 Direct Thermal/
Thermal Transfer Printer

S400 & S600



Applications

- Transport
- Health care
- Point-of-sale
- Manufacturing/distribution
- Professional/business use
- Automotive

Standard Features

- 32-bit RISC processor
- Auto-calibration
- Scalable fonts
- Color-coded operator cues
- Label tear-off feature
- Transmissive sensor
- Fully enclosed 8" (203.2mm) media compartment
- Prints width: 4.09" (104mm) maximum

S400:

- Print speed 2" (50mm), 3" (76.2mm), and 4" (101.6mm) per second, 203 dpi (8 dot/mm) print resolution

- 1MB DRAM memory

S600:

- Print speed 2" (50mm), 3" (76.2mm), 4" (101.6mm), 5" (127mm), and 6" (152.4mm) per second, 203 dpi (8 dot/mm)

- 2MB DRAM memory, 1MB Flash memory
- New technology printhead mechanism

PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
S400			
51008	S-400 Direct Thermal/Thermal Transfer, 115 VAC	20 lb	\$1,395.00
51012	S-400 Direct Thermal/Thermal Transfer w/auto peel option, 115VAC	20 lb	1,695.00
51009	S-400 Direct Thermal/Thermal Transfer, 230 VAC	20 lb	1,395.00
51013	S-400 Direct Thermal/Thermal Transfer w/auto peel option, 230 VAC	20 lb	1,695.00
S600			
51010	S-600 Direct Thermal/Thermal Transfer, 115 VAC	20 lb	1,795.00
51014	S-600 Direct Thermal/Thermal Transfer w/auto peel option, 115VAC	20 lb	2,095.00
51011	S-600 Direct Thermal/Thermal Transfer, 230 VAC	20 lb	1,795.00
51015	S-600 Direct Thermal/Thermal Transfer w/auto peel option, 230 VAC	20 lb	2,095.00
OPTIONS/ACCESSORIES			
51016	Expandable flash memory, 4MB		249.00
51017	Expandable flash memory, 8MB		399.00
46793	Bar-One® software		495.00
64786	Wireless transmitter receiver for printers, 2.46 GHz, includes RS-232 cable, power supply & software (requires a set of two or more)		495.00
51018	Additional operating manual, S-400/S-600		35.00
CABLES			
15552	Custom RS-232 cable		95.00
41501	6' serial cable (DB25 to DB25)		49.00
37527	6' parallel cable		29.00

ZEBRA S400 & S600 SPECIFICATIONS

PRINT CHARACTERISTICS

Print Speed:

S400: 2", 3", & 4" (50, 76.2, 101.6mm) per second

S600: 2", 3", 4", 5", & 6" (50, 76.2, 101.6, 127, & 152.4mm) per second

Resolution: 203 dpi (8 dots/mm)

Print Width: 4.09" (104mm) maximum

Print Length: 36" (914mm) maximum

RIBBON

Ribbon Width: 1.57" to 4.5" (39 to 114mm)

Ribbon Length: 1475' (450m)

Roll Diameter: 3.2" (81mm) O.D.

Core Size: 1" (25mm) I.D.

MEDIA

Media Thickness: 0.0023" to 0.0012" (0.058 to 0.305mm)

Media Width: 0.75" to 4.5" (19 to 114mm)

Supply Roll Capacity: 8" (203mm) maximum

Core Size: 3" (76mm)

Interlabel Gap: 0.08" to 0.16" (2 to 4mm); 0.118" (3mm) recommended

BAR CODES

Codes: Code 39, Code 11, Code 93, Code 128, Codabar, Plessey, LOGMARS, Interleaved, 2 of 5, EAN-8, EAN-13, Industrial 2 of 5, UPC-A, Standard 2 of 5, POSTNET, MSI, UCC/EAN 128, UPC/EAN with two- and five-digit supplements

INTERFACING

Parallel and serial communications

ELECTRICAL

115/230 VAC with a selection of power cords

APPROVALS

UL, CSA, CE mark

WARRANTY

One year limited warranty on parts, 6 months on printhead.