

Zebra® T402™ & DA402 Direct Thermal/Thermal Transfer Printers

PRINTERS
**DIRECT THERMAL/
THERMAL
TRANSFER**

Applications

- Transport
- Health care
- Point-of-sale
- Manufacturing/distribution
- Professional/business use

Standard Features

- 32-bit processor
- 1MB Flash memory
- BAR-ONE® Lite and Windows® Driver CD-ROM
- Starter roll of media (100 4" x 3" labels)
- Scalable fonts
- Auto calibration
- RS-232 serial and Centronics® compatible parallel interfaces
- Standard 1-D bar code and 2-D (Maxicode, PDF-417) symbologies
- Print width: 1" (25.4mm) - 4.09" (104mm)

T402 Direct Thermal/Thermal Transfer:

- Print speed: 2" (51mm) per-second, 203 dpi (8 dot/mm) print resolution

DA402 Direct Thermal only:

- Print speed: 1.5" (38mm), 2" (51mm), 2.5" (64mm) per second, 203 dpi (8 dot/mm) print resolution



T402 Direct Thermal/
Thermal Transfer Printer



DA402 Direct
Thermal Printer



PART #	DESCRIPTION	EST. SHIP WEIGHT	SUGGESTED LIST PRICE
T402			
62994	T402 Thermal Transfer, 115 VAC	5 lb	\$765.00
62995	T402 Direct Thermal, 115 VAC	5 lb	765.00
62996	T402 Thermal Transfer, 230 VAC	5 lb	765.00
62997	T402 Direct Thermal, 230 VAC	5 lb	765.00
63006	T402 Thermal Transfer, w/label peel option, 115 VAC	5 lb	800.00
63007	T402 Direct Thermal, w/label peel option, 115 VAC	5 lb	800.00
63008	T402 Thermal Transfer, w/label peel option, 230 VAC	5 lb	800.00
63009	T402 Direct Thermal, w/label peel option, 230 VAC	5 lb	800.00
DA402			
62998	DA402 Direct Thermal Printer, 115VAC	5 lb	645.00
62999	DA402 Direct Thermal Printer, 230VAC	5 lb	645.00
63010	DA402 Direct Thermal Printer, w/label peel option, 115VAC	5 lb	680.00
63011	DA402 Direct Thermal Printer, w/label peel option, 230VAC	5 lb	680.00
OPTIONS/ACCESSORIES			
64786	Wireless transmitter receiver for printers, 2.46 GHz, includes RS-232 cable, power supply & software (requires a set of two or more)		495.00
CABLES			
15552	Custom RS-232 cable		95.00
37526	6' serial cable (DB9 to DB25)		29.00
37528	6' serial cable (DB9 to DB9)		29.00
37527	6' parallel cable		29.00

ZEBRA T402 & DA402 SPECIFICATIONS

PRINT CHARACTERISTICS

Print Speed:

1.5" to 2.5" (38 to 51mm) per second

Resolution: 203 dpi (8 dots/mm)

Print Width: 1.12" to 4.09" (28 to 104mm)

Print Length: 0.005" to 22" (0.125 to 559mm)

RIBBON

Ribbon Width:

T402: 1.3" to 4.3" (33 to 110mm)

Roll Diameter:

T402: 1.39" (35mm) O.D.

Core Size:

T402: 0.5" (13mm) I.D.

MEDIA

Media Thickness:

T402: 0.003" to 0.007" (0.08 to 0.18mm)

Media Width:

T402: 1.12" to 4.65" (28 to 118mm)

DA402: 1" to 4.25" (25.4 to 108mm)

Media Length:

T402: 0.38" to 22" (10 to 559mm)

DA402: 0.5" to 22" (13 to 559mm)

Supply Roll Capacity: 5.0" (127mm) maximum

Core Size:

1.0" (25.4mm)

Interlabel Gap:

T402: 0.08" to 0.16" (2 to 4mm); 0.118" (3mm) recommended

BAR CODES

Codes: Code 11, Code 39, Code 93, Code 128, Codabar, MSI, EAN-8, EAN-13, EAN Extensions, Interleaved 2 of 5, Industrial 2 of 5, Std 2 of 5, LOGMARS, POSTNET, EAN-14/UPC-A, UPC Extensions, Plessey, MicroPDF417, PDF-417, QR, Code 49, DataMatrix, MaxiCode

INTERFACING

Parallel and serial communications

ELECTRICAL

115/230 VAC with a selection of power cords

APPROVALS

UL, CSA, CE mark

WARRANTY

One year limited warranty on parts, six months on printhead.