

DEPARTMENT OF TRADE AND COMMERCE

OTTAWA.....August..20,...1964.

APPROVAL LISTING

EASTERN SCALE

WESTERN SCALE

CONTRACTOR'S PORTABLE TRUCK SCALE

Under the provisions of the Weights and Measures Act, Chapter 292, R.S.C. 1952, and Regulations thereunder (P.C. 6894), the apparatus specified and illustrated herein have been listed as approved devices and may be used in Canada in accordance with the conditions applicable.

Apparatus Listed:

Contractor's portable truck scales equipped with full capacity beam, type registering beam or cabinet dial, including model numbers as follows:

Single Unite	Split Frame Maximum	Tandem Connected	
Models Capacity	Models Capacity	Models Capacity	
2020PSR. 25 tons.	24035PSR, 45 tons.	2020-40PSR, 45 tons.	
3020FSR, 35 tons.	24040PSR, 45 tons.	3020-50PSR, 55 tons.	
3025PSR, 35 tons	25035PSR, 55 tons.	2525-50PSR, 55 tons.	
3030PSR, 35 tons.	25040PSR, 55 tons.	3030-50PSR, 55 tons.	
4030PSR, 45 tons	25050PSR, 55 tons.	3535-60PSR, 65 tons.	
4035PSR, 45 tons.	25060PSR, 55 tons.	2525-65PSR, 70 tons.	
5025PSR, 55 tons	26050PSR, 65 tons.	3030-65PSR, 70 tons.	
5035PSR, 55 tons	26060PSR, 65 tons.	3030-80PSR, 85 tons.	
	26550PSR, 70 tons.	2525-100PSR, 105 tons.	
	27060PSR, 75 tons.	3030-100PSR, 105 tons.	
		3535-100PSR, 105 tons.	
		3535-125PSR, 130 tons.	

Manufactured by Eastern Scale Works Limited, 30 Carnforth Road, Toronto 16, Ontario, and Western Scale Company Limited, 680 Industrial Avenue, Vancouver 10, B. C.

When the symbol CD is used after the model number it indicates cabinet dial head.

Rating of Apparatus:

From 10 to 130 tons.

Applications

Weighing sand, gravel and other construction materials when conditions are such that the scale must be moved from place to place.

..../

Conditions:

As prescribed in P.C. 6894 with the added requirement that the use of the scale in any one location shall be of a temporary nature.

Description:

These devices are constructed to allow contractors to move them to any desired location. The single unit is of the pipe lever design with two end torque type levers and a single extension pipe lever secured to the transfer arm and acting as the transfer lever. The split frame unit is a 3 section pips lever design made up of the single unit and one section connected with a long pipe transfer lever. The tandem unit is made up of two complete single lever units with the transfer lover of each unit connected to a suitable common head or beam indicating the total capacity of the combined scale. The scales are for pitless installation and may be equipped with wooden deck, steel deck or concrete deck. Each scale unit is mounted in a fabricated steel frame. The balance ball adjustment is operated by a separate tool.

The Dial Heads may or may not be supplied with ticket printers. Dial Heads are supplied by Detecto Scale Company, Brooklyn, New York, U.S.A.

Testings

The standard tests for a vehicle scale shall apply. Scales made up of two units shall be considered as 4 section scales for inspection purposes.

C. S. Phillips,

Chief, Weights and Measures Division,

Standards Branch.

Reference: SL-102-645

R. W. MacLean, _ Director,

Standards Branch.

The second secon					
	mana sa s			*	