



PRODUCTS
AT A
GLANCE



HX2



HX3



8650 Bluetooth
Ring Scanner



MX3Plus



MX8



MX7/MX7CS



MX9/MX9CS/
MX9HL



VX3Plus



VX6



VX7



VX8



VX9

DESCRIPTION	Wearable On Wrist or Waist	Wearable, Voice-Only Computer	Wearable Ring Scanner	Hybrid Tablet Handheld With QWERTY Keyboard	Smallest, Most Economical Handheld From LXE	Most Versatile Handheld MX7CS - Cold	Ultra-Rugged Handheld MX9CS - Cold MX9HL - HazLoc	Compact, Half Screen Vehicle Mount	Industry's Best Selling Half Screen Windows CE Vehicle Mount	Full Screen Windows CE Vehicle Mount	Full Featured Windows XP/XPE Vehicle Mount	Full Featured Windows XP/XPE Vehicle Mount
APPLICATIONS	-High Speed, High Volume Picking	-Voice Directed Applications	-Any Standard Range Scanning Applications	-Pick & Run -Cross Docking -WIP -Text Heavy Apps	-Receiving -Picking -Retail -Multi-Modal	-Warehousing -Manufacturing -Cold Storage -Multi-Modal	-Ultra-Rugged Indoor/Outdoor -Port Apps -Cold Storage	-Stand-Up Vehicles - Carts - Small Lift Trucks	-Warehousing -Manufacturing -Cold Storage	-Warehousing -Manufacturing -Cold Storage -Ports	-XP Apps -Warehouse -Cold Storage -Ports	-XP Apps -Warehouse -Cold Storage -Ports
OS	Windows CE 5.0	Windows CE 5.0		Windows CE 5.0	Windows CE 5.0 or Win. Mobile 6.1.5	Windows CE 5.0	Windows CE 5.0	Windows CE 5.0	Windows CE 5.0	Windows CE 5.0	Windows XP/XPE	Windows XP/XPE
CPU	400MHz	400MHz		400MHz	520MHz	400MHz	800MHz	400MHz	400MHz	400MHz	600MHz to 1.4GHz	600MHz to 1.4GHz
OPERATING TEMP	-4° to 122°F	❄ -40° to 122°F	-4° to 122°F	-4° to 122°F	14° to 122°F	❄ 14° to 122°F ❄ -22° to 122°F	❄ 14° to 122°F ❄ -22° to 122°F	-4° to 122°F	❄ -4° to 122°F ❄ -22° to 122°F	❄ -4° to 122°F ❄ -22° to 122°F	❄ -22° to 122°F	❄ -22° to 122°F
DROP SPEC/VIB.	4 ft. To Concrete	4 ft. To Concrete	4 ft. To Concrete	4 ft. To Concrete	4 ft. To Concrete	5 ft. To Concrete	6 ft. To Concrete	MIL STD 810F	MIL STD 810F	MIL STD 810F	MIL STD 810F	MIL STD 810F
IP RATING	54	54	54	66	54	65	67	66	66	66	65	54
I-SAFE/HAZ. LOC.							Class 1 Div II					
WEIGHT	9.3 oz	9.3 oz	4.8 oz	37.7 oz	13.3 oz	21 oz	34 oz	40 oz	9.4 lbs.	9.4 lbs.	7.7 lbs.	8.2 lbs.
COMPUTER SIZE	4.9" x 3.5" x 1.4"	4.9" x 3.5" 1.4"		8" x 6" x 1.9"	7.6" x 2.8" x 1.8"	8.8" x 3.4" x 2"	9.9" x 3.9" x 2.7"	9" x 6" x 2.2"	9.6" x 12.2" x 3.6"	9.6" x 12.2" x 3.6"	11" x 9" x 3"	12.2" x 9.8" x 3.5"
DISPLAY SIZE	2.5"			6.5"	2.8"	3.5"	3.7"	6.5"	10.5"	12.1"	10.4"	12.1"
DISPLAY SPECS	320 x 240 ¼ VGA 350 NIT			640 x 240 ½ VGA 350 NIT	240 x 320 ¼ VGA 300 NIT	240 x 320 ¼ VGA 280 NIT	240 x 320 ¼ VGA Outdoor - 200 NIT	640 x 240 ½ VGA 350 NIT	800 x 320 ½ SVGA Outdoor-550 NIT Indoor-350 NIT	800 x 600 SVGA Outdoor-550 NIT Indoor-350 NIT	800 x 600 SVGA Outdoor- 550 NIT Indoor- 400 NIT	800 x 600 SVGA 400 NIT 1024 x 768 XGA 320 NIT
OUTDOOR DISPLAY	Yes			Yes			Yes	Yes	Yes	Yes	Yes	
MEMORY - SD RAM	128MB	128MB		128MB	128MB	128MB	128MB	128MB	64MB or 128MB	64MB or 128MB	512-1024MB	512MB-1024MB
STORAGE	128MB or 512MB	128MB or 512MB		128MB	128MB - 1GB	128MB - 1GB	128MB - 4GB	128MB	64MB or 128MB	64MB or 128MB	2 GB & 4 GB Flash, 60GB Rotating	2GB & 4GB Flash, 60GB Rotating
RADIO - WLAN	a/b/g - CCXv4	a/b/g - CCXv4		a/b/g - CCXv4	a/b/g - CCXv4	a/b/g - CCXv4	a/b/g - CCXv4	a/b/g - CCXv4	a/b/g - CCXv4	a/b/g - CCXv4	a/b/g	a/b/g
RADIO - WAN							Yes				Yes	Yes
RADIO - GPS							Yes					
RADIO - BLUETOOTH	2.0 EDR	2.0 EDR	2.0 EDR	2.0 EDR	2.0 EDR	2.0 EDR	2.0 EDR	2.0 EDR	2.0 EDR	2.0 EDR	2.0 EDR	2.0 EDR
POWER	Full & Extended Shift	Full & Extended Shift	2x & 3x Full Shift	Full Shift	Full Shift	Full Shift Cold: 2.5 Hours	Full Shift Cold: Half Shift	12-80 VDC Internal Fully Isolated Power Supply	12-80 VDC Internal Fully Isolated Power Supply	12-80 VDC Internal Fully Isolated Power Supply	10-150 VDC	10-150 VDC
SHORT RANGE SCAN	Yes	Yes	Yes	Yes	Yes & Base	Yes & Base	Yes	Yes	Yes	Yes	Yes	Yes
ALL RANGE SCAN						Yes	Yes	Yes	Yes	Yes	Yes	Yes
IMAGERS	1D & 2D	1D & 2D	1D & 2D		1D & 2D	1D & 2D	2D	Yes	Yes	Yes	Yes	Yes
VOICE ENABLED	Yes	Yes		Yes	Yes	Yes	Yes	Yes	Yes	Yes		