


CAT-2 Heavy-Duty Label Rewinders

LABELMATE's Constant Adjustable Torque™ ("CAT") technology has made the silent and easy-to-use **CAT-2** the "Industry Standard" Label Rewinder. No awkward dancer arms, troublesome belts or clutches are used. Instead, a powerful direct drive motor, designed especially for this application and driven by advanced control circuitry, ensures constant, uniform rewind torque. The result is a short leader length, exceptionally easy threading, no speed adjustments, trouble-free performance, and unsurpassed reliability! A Torque Control knob allows you to set precisely the amount of rewind force desired. The bi-directional **CAT-2** adjusts automatically to any printer speed and even allows for back-feeding labels if your printer requires it. While the **CAT-2** Rewinders can also be used as label Unwinders, be sure to check out our complete line of dedicated Unwinders too.



The LABELMATE Heavy-Duty "CAT" Rewinders are designed for continuous duty operation in rugged environments. Maximum label web widths of 6-, 9 1/2-, or even 16-inches (See separate Data Sheet for the wide-web **CAT-16**) can be accommodated depending on the model Rewinder you choose. With the Model **CAT-2-R16**, label rolls up to 16-inches in diameter can be rewound. Model **CAT-2-ACH** includes an Adjustable Core Holder that accepts any core size from 1-inch to 4-inches in diameter and up to 6-inches in width. The **CAT-2** handles any rewind job and with its "HIGH" torque range can also power the LABELMATE **S-100** and **S-200** Label Slitters.

Rugged heavy steel, industrial quality construction allows the **CAT-2** to be simply set in place. Special anti-slip feet prevent the unit from moving. Reliable, high quality and maintenance-free, the Heavy-Duty **CAT-2** Label Rewinders feature a 3-Year Parts and Labor Limited Warranty, the longest in the industry! Put LABELMATE **CAT-2** Label Rewinders to work for you today and enjoy a new dimension in label rewinding convenience and reliability.

FULL SIZE "CAT-2" HEAVY-DUTY LABEL REWINDERS – "The Industry Standard"

MODEL	ADD SUFFIX	DESCRIPTION	WIDTH	DIAM.	SPEED
CAT-2	(NONE)	The "Industry Standard" Heavy-duty Rewinder for 3" cores. Powerful dual torque ranges. Bi-directional. Adjustable "TORQUE" Control. External "HALT" Control.	Up to 6"	Up to 12"	Up to 30 ips (inches per second)
	-1-INCH	<i>New!</i> CAT-2 for 1" diameter cores.	Up to 6"	Up to 12"	Up to 30 ips
	-W9	CAT-2 for labels up to 9.5" wide. 3" cores.	Up to 9.5"	Up to 12"	Up to 30 ips
	-ACH	CAT-2 with Adjustable Core Holder for any core size 1" to 4" in diameter. Single inner flange. Use APG-1 or SP-ACH if an outer flange is desired.	Up to 6"	Up to 11"	Up to 30 ips
	-CHUCK	<i>New!</i> CAT-2 with 3" diameter "Quick-Chuck"™ *	Up to 6.5"	Up to 12"	Up to 30 ips
	-R16	CAT-2 with 16" roll diameter and extra power.	Up to 6"	Up to 16"	Up to 30 ips
	-R16-CHUCK	<i>New!</i> CAT-2-R16 with 3" diameter "Quick-Chuck"™ *	Up to 6.5"	Up to 16"	Up to 30 ips
APG-1	(NONE)	Adjustable Paper Guide for CAT-2-ACH, or CAT-2-CHUCK. Guides outer edge of label to ensure an even roll edge.	N/A	N/A	Installs in minutes.
ADAPT-326	<i>New!</i>	Adapter allows use of 6" dia. Core on 3" dia. CAT-2-CHUCK			Per pair.

□CHUCK Models are also available with a 1-1/2", 40mm or 70mm diameter "Quick-Chuck"™ at the same price. Specify when ordering.

SPECIFICATIONS:


All models are bi-directional. "TORQUE ADJUST" - Continuously adjustable torque and braking control; "TORQUE RANGE" - NORMAL (REWIND), HIGH (SLIT); "EXTERNAL HALT CONTROL" – External SPST control removes power to the motor and applies braking. Its use is optional not required for operation.

Dimensions: 12.75H x 15W x 12.5D" (324 x 381 x 318mm). CAT-2-R16: 18H x 15W x 18D"

Base plate footprint: 7 x 15" (180 x 356mm). **Weight:** Approximately 25-30lbs (11.3-13.6kg) depending on model.

Power Requirements: 120vac 60Hz 55 va. UL Listed Power Supply. 220-240vac also available at same price.

Warranty: 3-Year Parts and Labor Limited Warranty. (One [1] Year Limited Warranty on Power Supply Module.)




CAT-2
UP TO 6" WIDE LABELS
UP TO 12" DIAMETER



CAT-2- W9
UP TO 9-1/2" LABELS
UP TO 12" DIAMETER



CAT-2-ACH
FOR 1" TO 4" DIAMETER CORES
SHOWN WITH APG-1 PAPER GUIDE



CAT-2-R16
6" WIDTH with
16" ROLL CAPACITY

Specifications are subject to change without notice. DATACAT2.doc 01/01

The World's Leading Manufacturer of Label Rewinders, Unwinders, Slitters and Core Chucks

LABELMATE LLC, 12A SUNSET WAY, HENDERSON, NV 89014-2002 USA

Toll-Free! (877) 833-7149 (702) 435-8535 FAX (702) 435-8536 www.labelmate.com E-mail: info@labelmate.com

LABELMATE EUROPE, 69 AVENUE ALPHONSE XIII, B-1180 BRUSSELS, BELGIUM +32 (2) 375-6960 FAX +32 (2) 375-3896