


LABELMATE

S-100 & S-200 Heavy-duty LABEL SLITTERS

LABELMATE Label Slitters allow you to print small labels several across ("up") and then slit them to the desired width. This multiplies your print efficiency by a factor equal to the number of labels across, and increases your print head life and ribbon usage efficiency dramatically.

The LABELMATE S-100 and S-200 are rugged High-Speed, Heavy-Duty Label Slitters identical in construction except for size. They are used with a LABELMATE CAT-2 Label Rewinder, and optionally, with a UCAT Label Unwinder. The Rewinder pulls the label web through the cutting blades and rewinds the slit labels. The Slitters can be used either "in-line" or "off-line". In "in-line" use, the Slitter is placed between the printer output and the Label Rewinder. The slitting speed is determined by the printer output speed. In "off-line" use, the Slitter is placed between a UCAT-1 Unwinder and a CAT-2 Rewinder. With slitting speeds up to 30-ips (80cm/sec) in "off-line" mode, you'll make fast work of big slitting jobs.



S-200 shown with 3 blades & optional PC-1 Pre-set Counter

An optional six- (6) digit Pre-set Label Counter allows you to set the number of labels to be slit. When the counter reaches the preset number, it sends a "HALT" signal to the CAT-2 Rewinder. Power to the CAT-2 rewind motor is then shut off and braking is applied. You'll have no annoying label spills to contend with.

The inexpensive, easily replaced snap-knife slitting blades are click-adjustable, extending their useful life. No tools are required for blade adjustment or replacement. During the slitting operation, the blades are stabilized with a proprietary system, giving a clean cut at all speeds. Rugged, heavy-gauge welded steel construction and precision parts yield a product of the highest quality. Put a LABELMATE Heavy-Duty Label Slitter to work for you, today!

SPECIFICATIONS:

	<u>S-100 Label Slitter</u>	<u>S-200 Label Slitter</u>
Size: HxWxD	12x12x12-inches (305x305x305mm).	15x15x15-inches (381x381x381mm).
Label Width:	Up to 6.5-inches (165mm).	Up to 10-inches (254 mm).
Number of blades:	2 included. Recommended max. 6	3 included. Recommended max. 6
Speed:	Same as printer speed for in-line use. Up to 30-ips (80cm/sec) in off-line use.	
Blade Holders:	Additional Blade Holders Model BH-1 are field installable. Includes blade.	
Power:	No power is required.	
Optional:	HSB-10 Precision High Speed Cutter Replacement Blades give longer life and better performance than standard blades. 10 blades supplied in convenient dispenser.	
Optional:	Model PC-1 six- (6) digit Pre-set Counter to set batch size. 120vac 60 Hz power required.	
Warranty:	Limited 3-year Parts and Labor Warranty. One-year Warranty on Pre-Set Counter.	

New!

Separator Plates for your LABELMATE CAT-2 Label Rewinder. Precision milled anodized aluminum Spacer Plates keep your label rolls from sticking together after they have been slit. Choose Model "**SP-3INCH**" for use with 3-inch diameter cores. Choose Model "**SP-ACH**" for use with

The World's Leading Manufacturer of Quality Label Rewinders, Unwinders, and Slitters
LABELMATE LLC, 12A SUNSET WAY, SUITE 106, HENDERSON, NV 89014-2002 USA
(702) 435-8535 FAX (702) 435-8536 www.labelmate.com

LABELMATE EUROPE, 69 AVENUE ALPHONSE XIII, B-1180 BRUSSELS, BELGIUM (32) (2) 375-6960 FAX (32) (2) 375-3896
Specifications subject to change without notice.

DataSLIT Rev. 08/99

the LABELMATE ACH-1 Adjustable Core Holder that accepts cores from 1- to 4- inches in diameter. You will need the same number of Spacer Plates as you have blades on your Slitter.

The World's Leading Manufacturer of Quality Label Rewinders, Unwinders, and Slitters
LABELMATE LLC, 12A SUNSET WAY, SUITE 106, HENDERSON, NV 89014-2002 USA
(702) 435-8535 FAX (702) 435-8536 www.labelmate.com

LABELMATE EUROPE, 69 AVENUE ALPHONSE XIII, B-1180 BRUSSELS, BELGIUM (32) (2) 375-6960 FAX (32) (2) 375-3896
Specifications subject to change without notice.

DataSLIT Rev. 08/99