

CellScale RF and Serial Ports Setup Worksheet

Comm Port 1

C1 Function

☐ Off

☐ Terminal

☐ Host

Type ☐ MSI ☐ SMA Level 1 ☐ SMA Level 2

Standard

☐ RS-232

☐ RS-485

☐ RS-423

Mode

☐ Duplex

☐ Listen

☐ Talk

Data Bits

☐ 7

☐ 8

Parity

☐ None

☐ Even

☐ Odd

Baud Rate

☐ 9600☐ 115200

☐ 14400☐ 230400

☐ 19200☐ 300

☐ 28800☐ 600

☐ 38400☐ 1200

☐ 57600☐ 2400

☐ 76800☐ 4800

Protocol / Handshake

☐ None

☐ Xon/Xoff

☐ DCE

☐ DTE

☐ CTS/RTR

Control

☐ On Demand

☐ On CTS

☐ On Weight Change

☐ On Load

☐ On Set Point Trigger

☐ On Total

☐ Continuous

Interval

Motion Detection

☐ Enabled

☐ Disabled

Connection Notes

Strings

Start String (64 Chars Max)

End String (64)

Data String

512 Chars Max

Comm Port 2

C2 Function

☐ RF Modem

☐ Host

☐ Off

Network

0-31

SRC Address

1-254

Power Level

☐ High

☐ Low

Baud Rate

☐ Slow

☐ Med

☐ Fast

MasterSlave

☐ Master

☐ Slave

DST Address

Slave Only

Protocol / Handshake

☐ None

☐ Xon/Xoff

☐ DCE

☐ DTE

☐ CTS/RTR

Control

☐ On Demand

☐ On CTS

☐ On Weight Change

☐ On Load

☐ On Set Point Trigger

☐ On Total

☐ Continuous

Interval

Motion Detection

☐ Enabled

☐ Disabled

Connection Notes

Strings

Start String (64 Chars Max)

End String (64)

Data String

512 Chars Max

Comm Port 3

C3 Device Description

☐ MSI

☐ SMA Level 1

☐ SMA Level 2

☐ On Command

☐ On Weight Change

☐ On Load

☐ On Set Point Trigger

☐ On Total

☐ Continuous

Interval

Motion Detection

☐ Enabled

☐ Disabled

Data String
512 Chars Max

Start String (64 Chars Max)

End String (64)

Comm Port 4

C4 Device Description

☐ MSI

☐ SMA Level 1

☐ SMA Level 2

☐ On Command

☐ On Weight Change

☐ On Load

☐ On Set Point Trigger

☐ On Total

☐ Continuous

Interval

Motion Detection

☐ Enabled

☐ Disabled

Data String
512 Chars Max

Start String (64 Chars Max)

End String (64)

Comm Port 5

C5 Device Description

☐ MSI

☐ SMA Level 1

☐ SMA Level 2

☐ On Command

☐ On Weight Change

☐ On Load

☐ On Set Point Trigger

☐ On Total

☐ Continuous

Interval

Motion Detection

☐ Enabled

☐ Disabled

Data String
512 Chars Max

Start String (64 Chars Max)

End String (64)