

*** TB9 Ver4.0 -b2.0 ***

Interface : USB (02.01)

DIP Switch 1

SW 12345678
On *****
Off *

1,2= Emulation : Star Line/T
5,6= USB : Mode 0
8 = NE Sensor : Connect

Memory Switch

FEDCBA9876543210 HEX.
<0> 0000000000000000 0000
<1> 0000000000001000 0010
<2> 0000000000010100 0014
<3> 0000000000000001 0001
<4> 0000000000000000 0000
<5> 0000000000001010 000A
<6> 0000000000000000 0000
<7> 0001000100000000 1100
<8> 0000000000000000 0000
<9> 0000000000000000 0000

<0> 4 = Character Mode : Standard
<1> 9 = Top Margin : 15mm
<1> 8 = Black Mark Detect : Invalid
<1> 4 = Zero Style : Slashed Zero
<1> 3-0= Inter-Char : USA
<2> 5,4= Print Speed : Low Speed 1
<2> 2-0= Page : Normal
<3> F-8= ANK Pitch : 12 dot
<3> 4 = <CR> : Ignore
<3> 1 = Feed Pitch : 3mm
<3> 0= Printable Area : 104mm
<4> 2-0= Retract Time : 0.5sec x 10
<5> 7-0= Auto Loading Error : Invalid
<6> D = Auto Loading : Valid
<6> C = Retract : Storage/Internal
<6> 3-0=