

## Stainless Steel Bench Scale Bases

Model	WB06	WB15	WB30	WB60	WB75	WB150
Maximum Capacity	6 kg 15 lb	15 kg 30 lb	30 kg 60 lb	60 kg 120 lb	75 kg 150 lb	150 kg 300 lb
Readability Non-Legal-for-Trade at Maximum Capacity	0.0005 kg 0.001 lb	0.001 kg 0.002 lb	0.002 kg 0.005 lb	0.005 kg 0.01 lb		0.01 kg 0.02 lb
Recommended Legal- for-Trade Build (NTEP)	5 x 0.001 kg 10 x 0.002 lb	10 x 0.002 kg 25 x 0.005 lb	25 x 0.005 kg 50 x 0.01 lb	50 x 0.01 kg 100 x 0.02 lb		100 x 0.02 kg 250 x 0.05 lb
Maximum Back Weight *	2 kg 5 lb	5 kg 10 lb	7 kg 15 lb	10 kg 25 lb	25 kg 45 lb	35 kg 75 lb
Resolution	Up to 5,000 divisions Legal-for-Trade / Up to 15,000 divisions non-Legal-for-Trade					
Load Cell Capacity	11 kg	22 kg	45 kg	100 kg		200 kg
Dimensions w x h x d	230 x 230 x 80 mm 9 x 9 x 3 in	305 x 305 x 80 mm 12 x 12 x 3 in			455 x 455 x 105 mm 18 x 18 x 4 in	
Net Weight	5 kg 12 lb	9 kg 20 lb			24 kg 52 lb	
Shipping Weight	7 kg 16 lb	11 kg 24 lb			27 kg 59 lb	
Load Cell Cable	2 m/6 ft				3 m/10 ft	
Load Cell Type	Analog—single 350 ohm load cell, 2 mV/V					
Construction	Stainless steel frame/stainless steel platter					
Protection	NEMA 4/IP65					
Operating Temperature	-10° C to 4° C (14° F to 104° F) 10 to 95% humidity, non-condensing					
Recommended METTLER TOLEDO Terminals	PANTHER®, LYNX®, JAGUAR®, JAGXTREME™, ID7 (with analog scale card), LYNXBATCH®, and PUMA® terminals and SC counting scale (second analog scale kit required)					
Approvals	NTEP Class III, 5000d, COC #98-109A1; Industry Canada, 5000d, AM5359					

\*Back weight based on recommended Legal-for-Trade build.


### Options:

- 14-inch (356 mm) and 19-inch (483 mm) columns for the PANTHER terminal
- Portability cart
- Factory Mutual/CSA approved hazardous area versions available. Order as WB-X

Features	Benefits
Washdown construction	<ul style="list-style-type: none"> <li>■ Easy to clean and sanitize</li> <li>■ 100% stainless steel construction</li> <li>■ Removable platter for easy cleaning</li> <li>■ Drain holes in base to eliminate water retention</li> <li>■ Superior load cell protection</li> </ul>
Low profile	■ Easy to integrate into working environment
Overload protection	■ Designed with 150% safe overload; 300% ultimate overload protection
Adjustable feet	■ Easy to level the scale on uneven surfaces

Contact your local METTLER TOLEDO authorized distributor or sales office for further information.

## Designed for Light Washdown Environments



Produced in a  
Facility that is

