

High Precision Platforms

The METTLER TOLEDO High Precision K-Bases give the highest reproducibility at capacities from 30 lb up to 12,000 lb. They all come with the MonoBloc load cell in a stainless steel enclosure and internal calibration weight. Platforms are available in stainless steel, powder coated or galvanized.

Model	Capacity/Resolution (lb/kg)	Dimensions (in.)
KA15s	30 lb/0.0002 lb (15 kg/0.1 g)	13.8" x 11"
KA32s	70 lb/0.0002 lb (32 kg/0.1 g)	13.8" x 11"
KB60.2	120 lb/0.002 lb (60 kg/1 g)	20" x 16"
KCC150	300 lb/0.002 lb (150 kg/1 g)	32" x 24"
KCC300	600 lb/0.005 lb (300 kg/2 g)	32" x 24"
KC300	600 lb/0.005 lb (300 kg/2 g)	39" x 32"
KCS300	600 lb/0.005 lb (300 kg/2 g)	32" x 32"
KC600	1200 lb/0.02 lb (600 kg/10 g)	39" x 32"
KCS600	1200 lb/0.02 lb (600 kg/10 g)	32" x 32"
KD600	1200 lb/0.02 lb (600 kg/10 g)	49" x 39"
KD1500	3000 lb/0.05 lb (1500 kg/20 g)	49" x 39"
KE1500	3000 lb/0.05 lb (1500 kg/20 g)	59" x 49"
KES1500	3000 lb/0.05 lb (1500 kg/20 g)	59" x 59"
KE3000	6000 lb/0.1 lb (3000 kg/50 g)	59" x 49"
KES3000	6000 lb/0.1 lb (3000 kg/50 g)	59" x 59"
KG3000	6000 lb/0.1 lb (3000 kg/50 g)	79" x 59"
KG6000	12,000 lb/0.2 lb (6000 kg/100 g)	79" x 59"

Special Models


Model	Capacity/Readability (lb/kg)	Dimensions (in.)	Type
KN1500	3000 lb/0.05 lb (1500 kg/20 g)	59" x 49"	Low profile
KES1500	3000 lb/0.05 lb (1500 kg/20 g)	59" x 49"	Lift deck
KES3000	6000 lb/0.1 lb (3000 kg/50 g)	59" x 49"	Lift deck

Specifications


Degree of protection	■ IP67 equal to NEMA 4X/6
Ambient temperature	■ -14 to 104°F accuracy class III ■ 32 to 104°F accuracy class II
Scale interface	■ IDNet
Approvals	■ NTEP, ISO9001, CE

Contact your local METTLER TOLEDO authorized distributor or sales office for further information.

**Highest
Reproducibility
for Capacities
30 lb to 12,000 lb**



Low Profile KN1500



Lift Deck KES1500



Produced in a
Facility that is