

WILDCAT®

W W Models
Have
Wheels for
Mobility!

Portable Bench Scales

Designed for
Portability
and
Economy

Models	WS30R	WS60R	WS60LR	WS150R	WW250VR	WW500VR
Maximum Capacity	30 kg 60 lb	60 kg 150 lb		150 kg 300 lb	250 kg 500 lb	500 kg 1000 lb
Readability Non-Legal-for-Trade at Maximum Capacity	0.005 kg 0.01 lb	0.01 kg 0.02 lb		0.02 kg 0.05 lb	0.05 kg 0.1 lb	0.1 kg 0.2 lb
Recommended Legal-for-Trade Build	30 x 0.01 kg 60 x 0.02 lb	60 x 0.02 kg 150 x 0.05 lb		150 x 0.05 kg 300 x 0.1 lb	250 x 0.1 kg 500 x 0.2 lb	500 x 0.2 kg 1000 x 0.5 lb
Maximum Back Weight*	30 kg 70 lb	10 kg 4 lb		30 kg 95 lb		
Resolution Legal-for-Trade Non-Legal-for-Trade	3000 divisions 10,000 divisions				2500 div 5000 div	2000 div 5000 div
Load Cell Capacity	100 kg			250 kg	500 kg	1000 kg
Base Dimensions w x d x h	305 x 355 x (95-110) mm 12 x 14 x (3.8-4.3) in		400 x 500 x (105-120) mm 15.7 x 19.7 x (4.1-4.6) in		508 x 711x 198 mm 20 x 28 x 7.8 in	
Scale Dimensions w x d x h	305 x 500 x (540-555) mm 12 x 19.7 x (21.3-2)2 in		400 x 650 x (885-990) mm 15.7 x 25.6 x (34.8-35.3) in		508 x 851 x 1321mm 20 x 33.5 x 52 in	
Column Height	350 mm/14 in		700 mm/28 in		1118 mm/44 in	
Net Weight	11 kg/24 lb		22 kg/49 lb		50 kg/110 lb	
Shipping Weight	14 kg/31 lb		30 kg/66 lb		51 kg/112 lb	
Construction	Terminal: ABS plastic; Column: Stainless steel (WS) / Painted steel (WW) Base: Polyurethane painted mild steel Platter: 304 stainless steel Wheels: WW models – Polyurethane					
Protection	General purpose, dry. Load cell is moisture- and dust-resistant.					
Display	Six-digit, 25 mm / 1 in tall, high contrast, LCD					
Keypad	Zero, Tare, Function, and Print					
Power	10.2 VDC / 0.15 A (AC transformer included) or six “D” cells Battery life: up to 500 hours					
Operating Temperature	-10°C to 40°C (14°F to 104°F) 10 to 95% relative humidity, non-condensing					
Data Output	RS-232					
Weighing Units	g, kg, lb					
Approvals	(WW models pending) NTEP Class III, COC #99-053; Industry Canada, AM5319; UL listed					



* Back weight based on recommended Legal-for-Trade build

Options:

- Display back light (Standard on U.S. units with the letter "V" in the model number)

Features	Benefits
Plug and play	■ WILDCAT scale is ready to weigh – no wiring or programming.
High contrast LCD display	■ Unmistakable results – fewer operator mistakes.
AC or battery operation	■ Portability – take the scale to the application.
RS232 data output	■ Document transactions, create records.
Wheels (WW models only)	■ 4 wheels for mobility and convenience – 2 with brakes.

Contact your local METTLER TOLEDO authorized distributor or sales office for further information.



Produced in a facility that is



METTLER TOLEDO

Specifications subject to change without notice.
©2001 Mettler-Toledo, Inc.
METTLER TOLEDO® and WILDCAT® are registered trademarks of Mettler-Toledo, Inc.

BP7067.2E