



Controller Specifications

Controller	8450	355	8461	UC-ST	8361
Keyboard	Tactile	Tactile	Touchscreen	Touchscreen	Touchscreen
Programmable Presets	48 Keys	48 Keys	350	350	1400
COOL Capability	No	No	Yes	Yes	Yes
NutriFacts/Safe-Handling	Yes	Yes	Yes	Yes	Yes
Display	Vacuum Florescent	Vacuum Florescent	LCD	LCD	LCD
Operating Range	32°F to 104°F 0°C to 40°C	32°F to 104°F 0°C to 40°C	41°F to 104°F 5°C to 40°C	41°F to 104°F 5°C to 40°C	41°F to 104°F 5°C to 40°C
Label Capacity	Standard	High Capacity	Standard	Standard	High Capacity
Label Sizes	1 to 7.9 in long and 1.6 (40mm) to 3.4 in (86mm) wide				
Controller Construction	Die cast aluminum base, plastic case	Stainless steel enclosure	Die cast aluminum base, plastic case	Die cast aluminum	Die cast aluminum base, plastic case

StepSaver® Specifications

Film Capacity	Three Rolls up to 20 in / 50.8 cm wide
Power	115 VAC, 60 Hz, 625 watts (excluding scale and printer)
Step-Saver® Construction	Stainless Steel
Scale Capacity	50 x .01 lb or 20 x .005 kg
Options	Stainless steel 12 x 24 in platter shelf (left-right), label dispenser rack

Mettler-Toledo USA
1900 Polaris Parkway
Columbus, Ohio 43240
TEL. (800) 883-2171
(614) 438-4511

Mettler-Toledo, Canada
TEL. (800) 263-6593

Mettler-Toledo S.A., Mexico
TEL. 52 55 5547 1634



Manufactured in a facility that is ISO9001 certified.

