IND560 Terminals

Custom Packaging Solutions
Simple Filling

CONSULTATIVE

Approvals:
- USA: Class II 100,000d, Class III/IIIL 10,000d: COC #05-010
- Canada: Class II 100,000d; Class III 10,000d, Class III HD, 20,000d: AM-5593

Standard Features:
- Mild Steel 16 "H X 16"W X 6" D enclosure*
- One RS232 serial port
- Analog or IDNet Interface
- Local I/O -4 Input / 6 Out Put
- 1-input and 1 E-Stop button

Optional
- Stainless Steel enclosure
- ControlNet, EtherNet/IP, RIO, Profibus
- Fill Option
- Programmable TaskExpert
- Discrete IO 4in/4out (include B in the Comm I/O slot)

Environmental Protection
- Mild Steel Enclosures TYPE 4X (16" x 16" x 6") *
  *Suitable for installation in a Class I and II, Div 2 area when installed according to Control Drawing
- 304 Stainless Steel Enclosures TYPE 4X (16"x 16"x 6")
- **X-Purge - Suitable for Class I & II; Divisions 1 & 2; Group C,D,E,F,G; T4 (No Agency Approval)**
  Must be approved locally.
- Flanged/Flush Mount Enclosures for use in limited space areas, pharmaceutical clean room. EZ Clean Control option available.
- Watershed™ NSF CO1 compliant enclosure for food processing/pharmaceutical applications

Standard Customizations
- One, two, or three panel mount terminals mounted in Stainless Steel enclosure.
- Instruments wired to Power Panel
- Drawings and Documentation (1 set with equipment, additional for a fee)
- Hazardous Area--X-Purge package

Custom Options
- Terminal packages do not include any instrument options. Options may be added at Suggested List Price.
- Manual operators and internal I/O.
- Custom installation or wiring of options.
- Additional Documentation

Contact Custom Systems Application Support for quotes.

IND780 Terminals

Custom Packaging Solutions

CONSULTATIVE

Approvals:

- USA: Class II 100,000d, Class III/IIIL 10,000d: COC #06-017
- Canada: Class II 100,000d; Class III 10,000d, Class III HD, 20,000d: AM-5592

Standard Features:

- Desk/Wall or Panel enclosure
- One RS232 serial port
- One RS232/422/485 serial port
- One Ethernet TCP/IP port (for PC)
- Graphical backlit LCD display
- 6 user selectable soft keys, CTPZ, and 4 application keys
- Flexible print templates
- Multiple serial protocols for easy connectivity
- USB Master for external keyboard

Optional

- Up to 4 simultaneous scales and SUM scale
- ControlNet, EtherNet/IP, RIO, Profibus
- Discrete IO 4in/4out (include B in the Comm I/O slot)
- Programmable TaskExpert

Environmental Protection

- Mild Steel Enclosures TYPE 4X (20"x20"x6") *
  *Suitable for installation in a Class I and II, Div 2 area when installed according to Control Drawing
- 304 Stainless Steel Enclosures TYPE 4X (20"x20"x6")
- **X-Purge - Suitable for Class I & II; Divisions 1 & 2; Group C,D,E,F,G; T4 (No Agency Approval) Must be approved locally. (24"x24"x8")**
- Flanged/Flush Mount Enclosures for use in limited space areas, pharmaceutical clean room. EZ Clean Control option available.
- Watershed™ NSF CO1 compliant enclosure for food processing/pharmaceutical applications

Standard Customizations

- One, two, or three panel mount terminals mounted in Stainless Steel enclosure.
- Instruments wired to Power Panel
- Drawings and Documentation (1 set with equipment, additional for a fee)
- Hazardous Area--X-Purge package

Custom Options

- Terminal packages do not include any instrument options. Options may be added at Suggested List Price.
- Manual operators and internal I/O.
- Custom installation or wiring of options.
- Additional Documentation

Contact Custom Systems Application Support for quotes.

 ©Mettler-Toledo, LLC

Terminal Packages

Custom In-Wall packages						
CF560P1000000	16"	16"	6"	IND560	10V	$6,715
CFEZ560P1000	16"	16"	6"	IND560	10V	$8,908

*External dimensions (does not include flange when applicable)

Custom Systems Terminal Options

CUSTOM OPTIONS AVAILABLE ON REQUEST

Order Number	Description	Suggested List Price (CDN$)
FLUSH MOUNT	Flanged, in wall-mounting modification of standard custom enclosure.	Call
Custom Cabinet	Increase cabinet size to the next FF designation ("A" to "B", "B" to "C", etc.)	Call
EZ CLEAN	EZ-Clean Controls Mounted in Fast Factory Enclosure	Call
Push-button/Lights	Push-button,Safe area, specify color (Black, Red, Green) and nameplate(Start, Stop, Discharge, Clear, Jog, Print, Hold, Select, etc.)	Call
7/9 Push Button/Lights	Push Button for use in Div I area.	Call
Push-Button	Mushroom Head Push-Button, Safe Area - 2 position maintained , red	Call
7/9 Push-Button	Mushroom Head Push-Button, Div 1 Area - 2 position maintained , red	Call
Switch	Selector Switch - Specify keyed or non-keyed and number of positions (1, 2, or 3), Safe Area	Call
Push-Button Stations		
TYPE PB(1)	TYPE 7/9 Push-button station, 1 push-button (specify function)	Call
TYPE PB(2)	TYPE 7/9 Push-button station, 2 push-buttons (specify function)(Example: Start/Stop)	Call
TYPE PB(3)	TYPE 7/9 Push-button station, 3 push-buttons (specify function)	Call
TYPE PB(4)	TYPE 7/9 Push-button station, 4 push-buttons (specify function)(Example: CTPZ—Clear, Tare, Print, Zero)	Call
PB(2)	Mild steel enclosure, 2 push-buttons (specify function)	Call
PB(2) SS	304 Stainless steel enclosure, 2 push-buttons (specify function)	Call
PB(4)	Mild steel enclosure, 4 push-buttons (specify function)	Call
PB(4) SS	304 Stainless steel enclosure, 4 push-buttons (specify function)	Call

Notes

 ©Mettler-Toledo, LLC