# **DP-6700**

# **Bench/Receiving Scale**





An excellent, easy to use, digital scale for wet environments, such as meat and seafood processing plants. Four standard functions make accurate checkweighing, packing, grading and piece counts quick and painless.

The DP-6700's large, tilting display makes it easy to read from any angle or distance.

#### **Features**

- Large LCD Display with Annunciators
- Functions: Checkweighing, Grading, Packing, Counting and Weigh Totals
- Under/Accept/Over Annunciator
- Large Stainless Steel Platform
- Push Button Tare
- Battery and AC/DC Operation
- · Adjustable Auto Shut-off
- Washdown (NEMA 4/IP65 when battery operated and AC jack is sealed)
- Tilting Indicator
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms

## **Options**

- AC/DC Adaptor (not washdown)
- ZBee Wireless
- · USB Flash Drive

#### **Features**



- Large LCD Display with Annunciators
- Functions: Checkweighing, Grading, Packing, Counting and Weigh Totals
- Under/Accept/Over Annunciator
- Large Stainless Steel Platform
- Push Button Tare
- Battery and AC/DC Operation
- Adjustable Auto Shut-off
- Washdown (NEMA 4/IP65 when battery operated and AC jack is sealed)
- Tilting Indicator
- Initial, Automatic and Semi-automatic Zero Setting Mechanisms

## **Options**

- AC/DC Adaptor (not washdown)
- ZBee Wireless
- USB Flash Drive

### **Specifications**

Accuracy	3000 Divisions		
Model	DP-6700-60	DP-6700-150	DP-6700-300
Capacity and Divisions	30 kg x 0.01 kg 60 lb x 0.02 lb 960 oz x 0.5 oz 60 lb x 0.5 oz	60 kg x 0.02 kg 150 lb x 0.05 lb 2400 oz x 1 oz 150 lb x 1 oz	150 kg x 0.05 kg 300 lb x 0.1 lb 4800 oz x 2 oz 300 lb x 2 oz
Weighing System	Strain gauge load cell		
Platform	13.7" x 21.6" stainless steel (350 mm x 550 mm)		
Display	LCD: 5 digits plus annunciators Character size: 1.8" x 0.9" (45 mm x 23.5 mm)		
Power	4 "D" batteries, optional AC adaptor (not washdown)		
Battery Life	1400 hours of continuous use with alkaline batteries		
Operating Temperatures	$14^{\circ}  \text{F} \sim 104^{\circ}  \text{F}  (-10^{\circ}  \text{C} \sim +40^{\circ}  \text{C})$		





Yamato Corporation 1775 S. Murray Blvd., Colorado Springs, CO 80916 U.S.A. Tel: 719.591.1500 Fax: 719.591.1045

Tel: 604.533.2338 Fax: 604.533.0827

Yamato Tech Corporation #112-19425 Langley By-Pass Surrey, B.C. V3S 6K1 Canada